

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-4-35  
Relating to Approval of New Motor Vehicles

INTERNATIONAL HARVESTER COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 39150 and 39151 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Section 39023 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That International Harvester Company 1976 model-year gasoline-powered engines in heavy-duty motor vehicles are approved for the engine family described below:

<u>Family</u>	<u>Engine Size CID</u>	<u>Engine Model</u>	<u>Exhaust Emission Control System</u>
V-392 Calif.	391	V-392	Engine Modifications and Exhaust Gas Recirculation

Section 39152, Part I, Division 26 of the California Health and Safety Code requires that the manufacturer affix a decal to the side window to the rear of the driver or, if there is no such window on the driver's side, to the windshield of the motor vehicle.

The following are the recommended values to be listed on the decal:

<u>Engine Family</u>	<u>Hydrocarbon plus Nitrogen Dioxide grams/brake horsepower-hour</u>	<u>Carbon Monoxide grams/brake horsepower-hour</u>
V392 Calif.	8	23

A supplemental information sheet is attached to this order which includes tune-up specifications and emission control system data.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 1 day of December, 1975.

*G. C. Hass*  
G. C. Hass, Chief  
Division of Vehicle  
Emissions Control

AIR RESOURCES BOARD  
 SUPPLEMENTAL INFORMATION  
 1976 MODEL YEAR  
 HEAVY-DUTY GASOLINE ENGINES

MANUFACTURER: INTERNATIONAL HARVESTER COMPANY		EXECUTIVE ORDER NO. A-4-35				PAGE NO. 1				
Engine Family	Engine Models	Engine CID	Distributor		Emission Control System		Tune-up Specifications			
			Type	Mfgr. Part No.	Type	Mfgr. Part No.	Idle RPM	Basic Timing	Idle Mixture	
V-392 Calif.	V-392	391	C, V	Holley Prestolite 467034-C91 467035-C91	1-4V	Holley 461310-C91	EM, EGR	440307-C1 I-12,000 miles	625-675 RPM in neutral TDC @ 675 RPM in neutral	0.5-1.5% CO

Abbreviations:

Distributor  
 C - Centrifugal Advance  
 V - Vacuum Advance  
 VR - Vacuum Retard  
 EI - Electronic Ignition

Exhaust Emission Control System

AJ - Air Injection  
 EGR - Exhaust Gas Recirculation  
 EM - Engine Modifications

\*Service

I - Inspection, repair, replace as needed  
 R - Replace