## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-13-26 Relating to Certification of New Motor Vehicle Engines

## CATERPILLAR TRACTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That Caterpillar Tractor Company 1978 modelyear diesel-powered engines in heavy-duty motor vehicles with manufacturer's gross vehicle weight rating greater than 8500 pounds are certified for the engine family, codes and models described below:

Family	Engine Size (CID)	<u>Type</u>	
11-Code B	893	Inline Six-Turbocharged	

Models and Engine Codes as listed in attachment.

Section 43200, Part 5, Division 26 of the California Health and Safety Code requires that the manufacturer affix a decal to the side window to the rear of the driver or, if there is no such window on the driver's side, to the windshield of the motor vehicle.

The decal shall display the applicable model year heavy-duty engine exhaust emission standards and the following recommended values:

Engine	HC + NOx	CO	HC	NOx
Family	gm/bhp-hr	gm/bhp-hr	gm/bhp-hr	gm/bhp-hr
11-Code B	Not Applicable	2	0.5	6.9

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 27 day of February, 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

Part Number  3406 Caterpillar Caterpillar 9N3839 9L6884 300 @	imum Fue Max 2100 rpm 164 116 1900 rpm 175	Rate at imum HP	Basic Initial Timing  22.5° BTDC Static
Engine Model Pump Mfgr. Part Number Part Number  Rate and  Caterpillar 9N3839  Caterpillar 9L6884  Rate 200  Rate 200  Rate 3406	2100 rpm 164 116 1900 rpm 175	at imum HP  mm <sup>3</sup> /str .5 lbs/hr  mm <sup>3</sup> /str	Initial Timing 22.5° BTD0
9N3839 Caterpillar 300 @	116 1900 rpm   175	mm <sup>3</sup> /str	22.5° BTDC Static

abbreviations

Type
NA - Natural Aspiration

TC - Turbocharged
TCA- Turbocharged and Aftercooled

Emission Control Systems
AC - Aftercooler
EGR - Exhaust Gas Recirculation

TD - Throttle Delay