State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-16 Relating to Certification of New Motor Vehicle Engines

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following Mitsubishi Motors Corporation 1979 model-year diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating greater than 8500 pounds:

Engine Family	Displacement Cubic Inches	Exhaust Emission Control Systems (Special Features)
6DR5	243	Engine Modification

Engine Models and Codes as listed on attachments.

Section 43200, Part 5, Division 26 of the California Health and Safety Code requires that the engine manufacturer furnish a decal with each engine sold or delivered to a vehicle manufacturer. The decal shall display the applicable model year heavy-duty engine exhaust emission standards and the following certification emission values:

Engine Hydrocarbons Family gm/bhp-hr		Carbon Monoxide gm/bhp-hr	Nitrogen Oxides gm/bhp-hr
6DR5	0.6	4	5.0

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30 day of October, 1978.

G. C. Hass, Chief

Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL ENGINES

Manufacturer _	Mitsubishi Motor	s Corporation		n	l
Engine Family	6DR5		Engine		age <u>1</u>
Emission Contr	rol Systems EN	1	Type		
Engine Model	Fuel Injection Pump Mfgr. Part Number	Injector Mfg. Part Number	Maximum Rated HP and RPM	Fuel Rate at Maximum 3 ^{HP} mm ³ /stroke	Basic Initial Timing
6DR50A	Nippondenso 31761-22030	Nippondenso 31361-18001	100 BHP @ 3700 RPM	42.5 (52 lb/hr)	18 ⁰ BTDC Static
					Dptional Procedure: 16 ⁰ BTDC Static See Service Manual.
Date of Issue - 10-	30-78		·		

....eviations

Type

NA - Natural Aspiration

TC - Turbocharged

TCA - Turbocharged and Aftercooled

Emission Control Systems AC - Aftercooler

EGR - Exhaust Gas Recirculation TD - Throttle Delay