## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-27-46 Relating to Certification of New Motor Vehicle Engines

## MACK TRUCKS, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following Mack Trucks, Inc. 1985 model-year diesel engines have shown compliance with the optional transient standards and are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating greater than 8500 pounds:

Displacement			Exhaust Emission Control Systems		
Engine Family Cubic Inches (Liters)			(Special Features)		
14	672	(11)	(Acceleration Smoke Puff Limiter) (Intercooler) (Turbocharger)		

Engine models and codes are listed on attachments.

The following are the certification emission values for these engine families:

Engine Family	Hydrocarbons gm/bhp-hr	Nitrogen Oxides gm/bhp-hr
14	0.5	4.3

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order. Executed at El Monte, California this 19th day of December, 1984.

Bob Cross for

K. D. Drachand, Chief Mobile Source Division

E.O. # \_\_\_\_\_\_A-27 -46

## 1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL ENGINES

Manufacturer	MACK TRUCKS	, INC.		Page	1.	
Engine Family	14		_CID(Liter)-Type672 In-line 6			
ECS and (Specia	1 Features)Turboch (Smoke	arged, Chassis Puff Limiter)	Charge Air Co	oled, Four-Va	lve Head	
Engine Model	Fuel Injection Pump Mfr. Part Number	Injector Mfr. Part Number	Maximum Rated HP and RPM	Fuel Rate at Maximum HP mm <sup>3</sup> /stroke	Label Ident.	
EC6-350	UTDS 313GCA5161-P6 313GCA5163-P6	UTDS 114GC39-P17 114GC39-P14	350 @ 1800	210.6	14	
C6-300	UTDS 313GCA5161-P8 313GCA5163-P8	UTDS 114GC39-P17	300 @ 1700	191.9	14	

REVISION NO. / 2	1		Τ			PAGE IS SATISFACTORY UNSATISFACTORY
DATE 1985 5/21 94	,					DATE EPA REP

051283