State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-42-19 Relating to Certification of New Heavy-Duty Motor Vehicle Engines

WHITE ENGINES, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following White Engines, Inc. 1987 model-year diesel engines have shown compliance with the transjent test procedures and standards and are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 8,500 pounds:

Engine Family	Displacement Cubic Inches (Liters)	Exhaust Emission Control Systems (Special Features)
HWE03.7FAA4	226 (3.7)	(Diesel Injection-Direct) (Turbocharger) (Intercooler)

Engine models and codes are listed on attachments.

The following are the certification emission values for these engine families:

Hydrocarbo Engine Family gm/bhp-hr		Carbon Monoxide gm/bhp-hr	Nitrogen Oxides gm/bhp-hr	Particulates gm/bhp-hr	
HWE03.7FAA4	0.91	2.7	5.8	0.5	

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this 17 day of February, 1987.

K. D. Drachand, Chief Mobile Source Division

E.O.# A-42-1	9
0	

198 7 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL ENGINES

mission Control Sys. and (Special Features)				Eng. Type DID, I-4, TA			
ission (Control Sys. an	d (Special Fea	tures) <u>Air</u>	to Air Unarge	ATT COOLE	1 [[] [] []	
Engine Model	Fuel Injection Pump Mfr. Part Number	Injector Mfr. Part Number	Maximum Rated HP at RPM	Fuel Rate mm ³ /stroke (lbs/Hr)	Maximum Rated Torque at RPM	Fuel Rate mm ³ /stroke (lbs/Hr)	
)T3.7HT	Robert Bosch 40-3053601	Stanadyne 40-3055260	107 HP 0 2800 RPM	71 (43.4)	255 @ 1800 RPM	83.8 (32.9)	
÷ ′				·			
		. * . *			; ;		
						•	