

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-4-164

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following Navistar International Transportation Corporation 1994 model diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 8,500 pounds:

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>		<u>Exhaust Emission Control Systems and Special Features</u>
RNV466D6D0TW (DT-466HT)	7.6	(466)	Turbocharger Charge Air Cooler Smoke Puff Limiter

Engine models and codes are listed on attachments.

The following are the certification emission standards for this engine family in grams per brake horsepower-hour:

<u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
1.3	15.5	5.0	0.10

The following are the certification emission values for this engine family in grams per brake horsepower-hour:

<u>Engine Family</u>	<u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
RNV466D6D0TW	0.3	0.9	4.9	0.10

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

NAVISTAR INTERNATIONAL TRANSPORTATION CORP.

EXECUTIVE ORDER A-4-164
(Page 2 of 2)

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 9th day of August, 1994.



R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1994 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL-STANDARD ENGINESPage 1 of 1

(DT46GHT)

Manufacturer Navistar International Transportation Corp. Engine Family RNV466D6DOTWDisplacement: 7.6 / Liters 466 / Cubic InchesMaximum Rated Power: 250 HP @ 2300 RPM Engine Configuration: I-6Ignition: Compression X Compression with Glow Plug Spark Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Diesel X M100 M85 CNG LNG LPG Other (specify) Diesel Cert Fuel: 13 CCR 2282 40 CFR 86.1313-90 40 CFR 86.1313-94 XPrimary Intended Service Class: LHD MHD X HHD Urban Bus Exhaust ECS (incl. MFI TC, CAC): EM-DI-TC CAC SPL
(Use abbreviations per SAE J1930 SRP91)

Engine Mode (Eng. Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm ³ /stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX / Catalytic Converter Part No.
A250 (A250)	250 @ 2300	123.3 (95.0)	Pumps 1823137C91 Nozzles 1823763C91			
A230 (A230)	230 @ 2300	113.4 (87.4)	Pumps 1823136C91 Nozzles 1823763C91			

Date Issued: Revisions:

17^00.03,pp10

17.00.03-10 DT466HT PLN4