

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-142

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Cummins Engine Company, Inc. 1996 model diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
TCE359D6DAAA (403G)	5.9 (359)	Oxidation Catalytic Converter Turbocharger Charge Air Cooler

Engine models and codes are listed on attachments.

The certification exhaust emission standards for this engine family in grams per brake horsepower-hour are:

<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
1.3	15.5	5.0	0.10

The certification exhaust emission values for this engine family in grams per brake horsepower-hour are:


<u>Engine Family</u>	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulates</u>
TCE359D6DAAA (403G)	0.3	1.9	4.4	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 27th day of November 1995.


R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL-STANDARD ENGINES

Manufacturer Cummins Engine Company, Inc. Engine Family (403G) TCE359D6DAAA
 Displacement: 5.9 Liters 359 Cubic Inches
 Maximum Rated Power: 160 HP @ 2600 RPM Engine Configuration: I-6
 Ignition: Compression Compression with Glow Plug Spark
 Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Diesel M100 M85
 CNG LNG LPG Other (specify) _____
 Diesel Cert Fuel: 13 CCR 2282 40 CFR 86.1313-90 40 CFR 86.1313-94
 Primary Intended Service Class: LHD MHD HHD Urban Bus
 Exhaust ECS (include MFI, TC, CAC): OC (TC, CAC)
 (use abbreviations per SAE J1930 SEP91)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm ³ / stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX / Catalytic Converter Part No.
B5.9-160 (1959)	148 @ 2600	73 (64)	FP:3921918 IN:3926817 IN:3922521	N/A	N/A	3926233 3929433
B5.9-175 (1550)	160 @ 2600	76 (66)	FP:3921920 IN:3926818 IN:3922518	N/A	N/A	3926233 3929433

Date Issued:

Revisions: _____

SUBMITTED
OCT 06 1995