(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-290-56

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

DETROIT DIESEL CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Detroit Diesel Corporation 1997 model diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

.

Engine Family	<u>Liters</u>	(Cubic Inches)	Exhaust Emission Control Systems and Special Features
VDD12.EJDARA (SERIES-60)	12.7	775	Charge Air Cooler Turbocharger Powertrain Control Module

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake-horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>	
<u>Hydrocarbon</u>	<u>Monoxide</u>			
1.3	15.5	5.0	0.10	

The following are the certification exhaust emission values for this engine family in grams per brake-horsepower-hour:

Engine	Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Family</u>	<u>Hydrocarbon</u>	<u>Monoxide</u>	_Oxides_	
VDD12.EJDAF (SERIES-60)		1.7	4.9	0.09

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

DETROIT DIESEL CORPORATION

ŕ

EXECUTIVE ORDER A-290-56 (Page 2 of 2)

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this // day of December 1996.

m

R. B. Summerfield, Chief Mobile Source Operations Division

17-VDD12.EJDARA-3A

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL-STANDARD ENGINES

Manufacturer: Detroit Diesel Corporation
Page 1 of 3

Displacement: 12.7 Liters
775 Cubic Inches

Maximum Rated Power: 500 HP @ 2100 RPM
Engine Configuration: I-6

Ignition: Compression _X_
Compression with Glow Plug _____ Spark _____

Fuel Type(s): Dedicated _X_
Flex-Fuel _____ Dual-Fuel _____ Diesel _X_
M100 ______ M85 ______

Dissel Cert Fuel: 13 CCR 2282 ______ 40 CFR 86.1313-90 _____ 40 CFR 86.1313-94 _X_
Primary Intended Service Class: LHD ______ MHD _____ HHD _X_
Urban Bus _________

Exhaust ECS (include. MFI, TC, CAC):
ECM/PCM, CAC, (TC)
Exclassing the state of the state of

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm ³ /Stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX/ Catalytic Converter Part No.
<u>12.7L</u>		· · · · · · · · · · · · · · · · · · ·				
lA	470@2100	220.1	5235575	23518645		
		(153.7)		23518743		
2A	470@1800	245.8	ĺ	1		
		(147.1)				
3A	430@2100	200.7		I		
		(140.2)				
4A	430@1800	224.2	Ì			
		(134.2)	ĺ	•		
5A	450@1800	235.4	ł			
		(140.9)	ĺ			
6A	375@1800	195.5				
		(117.0)				
7A	400@1800	208.5	[
		(124.8)	1	l		
8A	360@1800	187.6	1			
_		(112.3)		i.		
9A	370@1800	192.8				
		(115.4)		:		
1M	400@2100	186.7	Ì	ļ		
		(130.4)	+	\downarrow		

Date Issued: 10-01-96 Rev.:

17-VDD12.EJDARA-3B

E.O. No. A-290-56

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL-STANDARD ENGINES

Page 2 of 3

Manufacturer: Detroit Diesel Corporation	Page 2 of 3
	Engine Family: VDD12.EJDARA
Displacement: 12.7 Liters 775 Cubic Inches	
Maximum Rated Power: 500 HP @ 2100 RPM	Engine Configuration: I-6
Ignition: Compression X_ Compression with Glow Plug	Spark
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel	Diesel X M100 M85
CNG LNG LPG Other (specify)	
Diesel Cert Fuel: 13 CCR 2282 40 CFR 86.1313-90	40 CFR 86 1313-94 X
rimary Intended Service Class: LHD MHD HHD	X Urban Bus
Exhaust ECS (include. MFI, TC, CAC): ECM/PCM, CAC, (TC)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm3/Stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX/ Catalytic Converter Part No.
	CONTINUED					
1 B	470@2100	220.1	5235575	23518645		
		(153.7)		23518743		
2B	430@2100	200.7	i	1		
		(140.2)		1		
3B	430@1800	224.2	i i	ĺ		
		(134.2)		ı İ		
4B	400@2100	186.7		Í		
		(130.4)	İ			
5B	400@1800	208.5	Ì	1		
		(124.8)	ĺ			
6B	370@2100	172.7				
		(120.6)		1		
7B	370@1800	192.8		1		
		(115.4)				
8B	360@18 00	187.6		i		
		(112.3)				
9B	400 @1950	196.2		1		
		(127.2)				
10B	450@1800	235.4				
		(140.9)		1		
11B	375@1800	195.5				
		(117.0)	\downarrow	\downarrow		

٩

17-VDD12.EJDARA-3C

E.O. No. A-290-56

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET HEAVY-DUTY DIESEL-STANDARD ENGINES

Page 3 of 3

Manufacturer: Detroit Diesel Corporation	Engine Family: VDD12.EJDARA
Displacement: 12.7 Liters 775 Cubic Inches	
Maximum Rated Power: 500 HP @ 2100 RPM	Engine Configuration: I-6
Ignition: Compression X_ Compression with Glow Plug	Spark
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel	Diesel X M100 M85
CNG LNG LPG Other (specify))
Diesel Cert Fuel: 13 CCR 2282 40 CFR 86,1313-90	40 CFR 86 1313-94 Y
Primary Intended Service Class: LHD MHD HHI) X Urban Bus
Exhaust ECS (include. MFI, TC, CAC): ECM/PCM, CAC, (T	C)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm3/Stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX/ Catalytic Converter Part No.
	CONTINUED		······································	<u> </u>		
1C	500@2100	234.8	5235915	23518645		
		(164.0)		23518743		
2C	500@1800	258.1	1	4		
		(154.5)		, I		
3C	500@2100	234.8				
		(164.0)				
١D	470@2100	220.1				
		(153.7)	ł			
2D	470@1800	245.8				
		(147.1)	1			
3D	470@2100	220.1				
		(153.7)	v	÷ ¥		

Date Issued: 10-01-96 Rev.:

.