State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-4-206-2

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1998 model-year Navistar International Transportation Corporation diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	Engine <u>Liters</u>	Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features
WNVXH0530CCB	8.7	(531)	Turbocharger Charge Air Cooler Engine Control Module Oxidation Catalytic Converter

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
H <u>ydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
0.1	4.0	4.0	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 150 days following the issuance of Executive Order A-4-206, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this day of April 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

				10	0.001	275 @ 2000	A275C	A275C
	78	179	950 @ 1300	101				
1					0,061	2/5@2000	AF275C	AF275C
ĺ	70.5	161.9	860 @ 1300	101	160 8			
			(100.0	2/5@2000	AL275C	AL275C
	65.9	151.2	800 @ 1300	101	100 8	2		
L								
						7000 8 2000	AZSUC	A250C
1	00.0	151.2	800 @ 1300	93	138.8	2000		
╝	65.0						P. P. Survey and T. P. S.	I Eligina Coda
•	(lbs/hr)@peak torque Device Per SAE J	mnystroke@peak	(SEA Gross)	(lbs/hr) @ peak HP (for diesels only)	mm/stroke @ peak HP (for diesel only)	3.8HP@RPM (SAE Gross)	2 Engine Model	
	8.Fuel Rate:	7.Fuel Rate:		5.Fuel Rale:	4.Fuel Rate:		EPA Engine Family: WNXXHUSJULLE	EPA Engine Far
	•	INT 530E	Family Name:	Manufacturer Family N				
		ion	Process Code: New Submission	Process Code:		206-2	Manufacturer: Navistar A-4-206-2	Manufacturer: