State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-4-208-2

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1998 model-year Navistar International Transportation Corporation diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	Engine <u>Liters</u>	Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features
WNVXH0466CCB	7.6	(466)	Turbocharger Charge Air Cooler Engine Control Module Oxidation Catalytic Converter

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
0.5	4.4	3.8	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 150 days following the issuance of Executive Order A-4-208, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 2 day of April 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

LARGE ENGINE MUDEL SUMMARY

Process Code: New Submission Manufacturer: Navistar_A-4-208-2

DT-466E

8.Fuet Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930 7.Fuel Rate: mm/stroke@peak torque 6.Torque @ RPM (SEA Gross) Manufacturer Family Name: 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) mm/stroke @ peak HP (for diesel only) 4.Fuel Rate: 3.BHP@RPM (SAE Gross) EPA Engine Family: WNVXH0466CCB. 2.Engine Model 1.Engine Code

opon transfer o	2 Fracine Model	(SAE Gross)	לוונס ותפסות וסו)	77				
Englue Code	A.C.I.B.III.C	· · · · · · · · · · · · · · · · · · ·			1 0000	Coa	40.5	DI, ECM, TC,
		0000	2 00	0.69	430 @ 1500	0.00		
A175C	A175C	175 @ 2300	03.2					20,782
					105 @ 1500	912	46.2	DI, ECM, TC,
01000	A190C	190 @ 2300	96.0	74.4	400 @ 1200			CAC, OC
				0	500 @ 1450	100.2	50.9	DI, ECM, TC,
A210C	A210C	210 @ 2300	105.5	82.2	0541 m 070			CAC, OC
2								•
					005 60 1500	129.5	60.5	DF, ECM, TC,
0000	A230C	230 @ 2300	118.5	92.0	nnet @ eng	2004		CAC, OC
Aksuc								
							0.00	CT MOS IC
			0.40	75.4	520 @ 1450	100.2	48.2	חי בסייוי וכי
A195C	A195C	195 @ 2300	0.78	2	,			CAC, OC
								•
					COC @ 1450	117.0	57.2	DI, ECM, TC,
	00100	240 € 2300	105.5	82.2	CC+1 (m) COO			CAC OC
A210C	AZ 10C							