1

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-13-134

Relating to Certification of New Heavy-Duty Engines and Vehicles

CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43100, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Caterpillar, Inc. and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following 2000 model-year Caterpillar, Inc. diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle-weight-rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	•	lacement <u>Cubic Inches</u>	Exhaust Emission Control Systems and Special Features
YCPXH0729ERK	12.0	729	Turbocharger Charge Air Cooler Electronic Control Module

The engine models and codes are listed on attachments.

BE IT ORDERED AND RESOLVED: That the following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour under the Federal Test Procedure ("FTP") for Heavy-Duty Diesel Engines (Title 13, California Code of Regulations, Section 1956.8):

	Total	Carbon	Nitrogen	Particulate
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Matter</u>
"FTP"	1.3	15.5	4.0	0.10

BE IT FURTHER RESOLVED: That pursuant to the Settlement Agreement and any modifications thereof, the aforementioned engine family is also subject to the following emission standards, in grams per brake horsepower-hour, under the EURO III tests in the Settlement Agreement, and a "Not-to-Exceed" nitrogen oxides emission standard of 7.0 grams per brake horsepower-hour:

	Total	Carbon	Nitrogen	Particulate
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Matter</u>
"EURO III"	1.3	15.5	6.0	0.10

BE IT FURTHER RESOLVED: That the following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

	Total	Carbon	Nitrogen	Particulate
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Matter</u>
"FTP"	0.2	1.0	3.8	0.08
"EURO III"	0.1	0.5	4.8	0.04

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. The Settlement Agreement is in effect.
- 2. Caterpillar, Inc. is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this ______ day of December 1999.

Rochal Session of Ar R. B. Summerfield, Chief

Mobile Source Operations Division

Engine Model Sermary Form

EO: A-13-134

Manufacturer: CATERPILLAR INC.

Engine category: On-highway HDDE

EPA Engine Family. YCPXH0729ERK

Mfr Family Name: NA

Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930
Cert Eng '96	1	455 @ 1800	229	138.6	1650 @ 1200	290	117.9	EM DI TO COM 140
•	Τ.	430 @ 1800	231	140		300	121	֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓
7	Τ.	(6)	239	145		290	117	EM DICK FOW,
. τυ	7	(9)	238	144	1650 @ 1200	302	122	
4	7	(9)	211	128		258	104	
i Ou	Ţ.	(9)	231	140		300	5 5	
ı 0	Ţ	(9)	223	135	1550 @ 1200	273	110	
_ `	Ì,	(6)	228	138	1450 @ 1200	260	105	
∞ (ļ	(9)	223	135	1550 @ 1200	273	110	
on ;	•	(9)	223	135	1550 @ 1200	273	110	
0.;	t	(9)	228	138	1450 @ 1200	260	105) - - - - -
	1	(9)	225	136	1550 @ 1200	277	175	
12	1	(9)	226	137	1450 @ 1200	265	107	
<u></u>	1	425 @ 1800	225	136	1550 @ 1200	277	112	
14	1	425 @ 1800	226	137	1450 @ 1200	265	107	
15	1	(9)	226	137	_	265	107	
16	•	395 @ 1800	221	134	-	260	10 T	
17	C - 12	405 @ 1800	215	130) (e	285 285		
18	C - 12	410 @ 1800	220	133) (c	263		
19	C - 12	380 @ 1800	211	128	1450 @ 1200	250		
20	C - 12	395 @ 1800	210	127	•	260		
21	C - 12	355 @ 1800	201	122) (E	243	_	
22	C - 12	370 @ 1800	195	118	9 (6	243 243	0 0	
23	C - 12	425 @ 1800	225	136) (e	27.7		
24	C - 12	355 @ 1800	201	122	(6			
25	C - 12	380 @ 1800	211	128) (243	0,6	
26	C - 12	355 @ 1800	201	122) (230	104	DI, TC,
27	C - 12) (e	195	149	3) (243		ᅙ
28	0.13) (200	0 7	9) 1	243	86	EM, DI, TC, ECM
}	ı	3)	C _B	118	1350 @ 1200	243	86	EM, DI, TC, ECM
							1	€
							-	TC, GC, ECM
								,