

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-13-136

Relating to Certification of New Heavy-Duty Engines and Vehicles

CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43100, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Caterpillar, Inc. and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following 2000 model-year Caterpillar, Inc. diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle-weight-rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

<u>Engine Family</u>	<u>Displacement</u>		<u>Exhaust Emission Control Systems and Special Features</u>
	<u>Liters</u>	<u>Cubic Inches</u>	
YCPXH0967ERK	15.8	967	Turbocharger Charge Air Cooler Electronic Control Module

The engine models and codes are listed on attachments.

BE IT ORDERED AND RESOLVED: That the following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour under the Federal Test Procedure ("FTP") for Heavy-Duty Diesel Engines (Title 13, California Code of Regulations, Section 1956.8):

	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"FTP"	1.3	15.5	4.0	0.10

BE IT FURTHER RESOLVED: That pursuant to the Settlement Agreement and any modifications thereof, the aforementioned engine family is also subject to the following emission standards, in grams per brake horsepower-hour, under the EURO III tests in the Settlement Agreement, and a "Not-to-Exceed" nitrogen oxides emission standard of 7.0 grams per brake horsepower-hour:

	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"EURO III"	1.3	15.5	6.0	0.10

BE IT FURTHER RESOLVED: That the following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"FTP"	0.1	1.2	3.8	0.08
"EURO III"	0.1	0.4	5.7	0.03

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2035 et seq.).


BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

1. The Settlement Agreement is in effect.
2. Caterpillar, Inc. is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 16th day of December 1999.


for R. B. Summerfield, Chief
Mobile Source Operations Division

Engine Model Summary Form

EO: A-13-136

Manufacturer: **CATERPILLAR INC.**
 Engine category: **On-highway HDDE**
 EPA Engine Family: **YCPXH0967ERK**
 Mfr Family Name: **NA**
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
Note: Peak Hp and Peak Torque fuel rates are nominal values. Due to production engine avgs. these fuel rates may change.								
Cert Eng '97	3406	600 @ 1800	336	203.2	2050 @ 1200	370	149.5	EM, DI, TC, ECM,
1	3406	600 @ 1800	329	199.2	2050 @ 1200	379	153.0	EM, D ICAC , ECM,
2	3406	600 @ 1800	329	199.2	2050 @ 1200	379	153.0	EM, D ICAC , ECM,
3	3406	600 @ 1800	326	197.3	2050 @ 1200	375	151.5	EM, D ICAC , ECM,
4	3406	600 @ 1800	326	197.3	2050 @ 1200	375	151.5	EM, D ICAC , ECM,
5	3406	575 @ 1800	319	193.4	1850 @ 1200	342	138.1	EM, D ICAC , ECM,
6	3406	575 @ 1800	319	193.4	1850 @ 1200	342	138.1	EM, D ICAC , ECM,
7	3406	575 @ 1800	316	191.5	1850 @ 1200	339	136.8	EM, D ICAC , ECM,
8	3406	575 @ 1800	316	191.5	1850 @ 1200	339	136.8	EM, D ICAC , ECM,