## State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-13-132

# Relating to Certification of New Heavy-Duty Engines and Vehicles

### CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43100, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Caterpillar, Inc. and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following 2000 model-year Caterpillar, Inc. diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle-weight-rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

2

E to Early		lacement <u>Cubic Inches</u>	Exhaust Emission Control Systems and Special Features
Engine Family	LIGIS	Ouble monoo	
YCPXH0442HRK	7.2	442	Turbocharger Charge Air Cooler Electronic Control Module

The engine models and codes are listed on attachments.

BE IT ORDERED AND RESOLVED: That the following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour under the Federal Test Procedure ("FTP") for Heavy-Duty Diesel Engines (Title 13, California Code of Regulations, Section 1956.8):

	Total	Carbon	Nitrogen	Particulate		
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Matter</u>		
"FTP"	1.3	15.5	4.0	0.10		

BE IT FURTHER RESOLVED: That pursuant to the Settlement Agreement and any modifications thereof, the aforementioned engine family is also subject to the following emission standards, in grams per brake horsepower-hour, under the EURO III tests in the Settlement Agreement, and a "Not-to-Exceed" nitrogen oxides emission standard of 5.0 grams per brake horsepower-hour:

1.04

CATERPILLAR, INC.

1

	Total	Carbon	Nitrogen	Particulate
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Matter</u>
"EURO III"	1.3	15.5	4.0	0.10

BE IT FURTHER RESOLVED: That the following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

	Total	Carbon	Nitrogen	Particulate		
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Matter</u>		
"FTP"	0.6	1.2	3.8	0.09		
"EURO (III"	0.1	0.6	3.8	0.06		

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- The Settlement Agreement is in effect. 1.
- Caterpillar, Inc. is in compliance with all applicable 2. certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this  $-\frac{16^{24}}{16^{24}}$  day of December 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

# Engine Model Summary Form

Manutacturer: Engine category: EPA Engine Fam <b>i</b> y: Mfr Family Name: Process Code:	<b>`</b>
Manufacturer: Caterprinar IIIC. Engine category: On-highway MHDD EPA Engine Famiy. YCPXH0442HRK Mfr Family Name: NA Process Code: New Submission	
3.BHP@RPM	
4.Fuel Rate: mm/stroke @ peak HP (lbs/hr) @ peak HP	
5.Fuel Rate: (lbs/hr) @ peak HP	
6. Torque @ RPM	
7.Fuel Rate: mm/stroke@peak	
走の: A-13-13ス ate: 2peak 8.Fuel Rate: 9.E (lbs/hr)@peak torque Devic	)

						_	_	_	_	_	_	_	_	_	_	_	_	_		Cer		1.EN	1
13	i	12	د_ د_		10	ų	) (	8	7	C	ת	G		4	ω	• •	0	<u> </u>		Cert Eng '98		.Engine Code	
3126		3126	3120	2200	3126	3720	2200	3126	3126		3126	3126		3126	3126		3126	3120	20.00	3126		2.Eligine Moder	
1/5 @ 2200		207 @ 2300	2 10 W 21 2		210 @ 2200	017 m 017	00000 0000	230 @ 2200	0077 @ 002		250 @ 2200	0077 @ C17	275 0 2200	275 @ 2200	000 W 000	00000	300 @ 2200	0047 @ 000	0016 @ 066	330 @ 2400		(SAE GIUSS)	3.BHP@RPM
QY	80	86		A0	102		101	115		202	124		121	132		144	145		150	641	110		4.Fuel Rate: mm/stroke @ peak HP /for diesel only)
00.1	7 TG	72.8	1	78.7	C.C/		75.1	85.1		013	91.5		97.2	97.4		106.2	107.4	104 1	123	- NO. F	120.2		5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels onlv)
	420 m 1440	02U @ 1440		520 @ 1440	0441 @ 020	500 @ 1110	605 @ 1400	000 @ 1440		660 @ 1440	800 @ 1440		800 @ 1440	000 (0) 1440		800 @ 1440	000 000	060 @ 1110	860 <u>@</u> 1440		860 @ 1440		6.Torque @ RPM (SEA Gross)
	85	i c	101	100		102	711	1.00	130	129		122	153		164	152		165	100	100	168		mm/stroke@peak torque
	41.0	10.0	48 9	40.0		49.3	20.7		8 69	62.7		76.0	14.3	1.0	79.6	13.0		80.0	2.00	c 00	81.5		8.Fuel Rate: (lbs/hr)@peak torque
CAC	していて					DI, TC			DICIPO			DICITO						DICTIC.			EM, DI, TC, ECM,		8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930

.

2

÷