State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-325-29

Relating to Certification of New Medium-Duty Motor Vehicle Engines

GFI CONTROL SYSTEMS, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 2001 model-year GFI Control Systems, Inc. Otto-cycle engines are certified for use in medium-duty vehicles with a manufacturer's gross vehicle weight rating (GVWR) between 8,501 to 14,000 pounds:

Emission Standard Category: Ultra-Low-Emission Vehicle (ULEV)

Fuel Type: Dual-Fuel Liquefied Petroleum Gas (LPG) or Gasoline

| Engine Family | ~ | Displacement Subic Inches) | Exhaust Emission Control Systems and Special Features |
|---------------|-----|-------------------------------|--|
| 1G9XH06.87CP | 6.8 | (417) | Sequential Multiport Fuel Injection Dual Heated Oxygen Sensors Heated Oxygen Sensor Three Way Catalytic Converter |

Engine models and codes are listed on attachments.

The ULEV certification exhaust emission standards for this engine family in grams per brake horsepower-hour are:

| Non-Methane Hydrocarbons + Nitrogen Oxides | Carbon <u>Monoxide</u> | <u>Formaldehyde</u> |
|--|---------------------------|---------------------|
| 2.5 | 14.4 | 0.050 |

The ULEV certification exhaust emission values for this engine family in grams per brake horsepower-hour are: (The values in parentheses are for gasoline.)

| Non-Methane Hydrocarbons + Nitrogen Oxides | Carbon <u>Monoxide</u> | Formaldehyde |
|---|---------------------------|---------------|
| 1.7 (0.7) | 4.1 (2.4) | 0.000 (0.001) |

BE IT FURTHER RESOLVED: That the listed engine models are certified to the optional ULEV standards and test procedures applicable to incomplete and diesel medium-duty vehicles between 8,501 and 14,000 pounds GVWR pursuant to Title 13, California Code of Regulations, Section 1956.8(h).

BE IT FURTHER RESOLVED: That the listed engine models shall be subject to the in-use compliance provisions applicable to 1995 and subsequent model-year medium-duty vehicle engines set forth in Title 13, California Code of Regulations, Section 2139(c).

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed engine models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That the listed engine models comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Sections 1965).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this ______ day of August 2000.

R. B. Summerfield, Chief

Mobile Source Operations Division

Engine IV Jel Summary Datal Se

3.BHP@RPM (SAE Gross)

2.Engine Model V 10 GFP

1.Engine Code

amily

orbatabase

4.Fuel Rate: mw/stroke @ peak HP (for diesel only)

¥

310 @ 4250

1F717H0B00/6F4 P1P02

17CP

5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)

425@3250

6.Torque @ RPM (SEA Gross)

Z

7.Fuel Rate; mm/stroke@peak forque

8.Fuel Rate: 9.Emission Contro (lbs/ln)@peak torque Device Per SAE J19

119 lbs/hr

SF1, 24025, HOZS, TWC.

444mm/stroke