

## INTERNATIONAL TRUCK AND ENGINE CORPORATION

EXECUTIVE ORDER A-004-0246-1 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC) Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZE (liter)	FUEL TYPE	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS	
2001	1NVXH0466ANB	7.6	DIESEL	DIESEL	Medium-Heavy- Duty	
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			ENGINE MODELS / CODES (rated power in horsepower, hp)			
DDI, ECM, TC, CAC						
ABBRÉVIATIONS: OC=oxidizing catalyst TWC=three-way catalyst O2S=oxygen sensor H02S=heated 02S DDI=direct dilesel injection IDI=indirect dilesel injection TC:SC=turbo/super charger CAC=charge air cooler SPL=smoke puff limiter PCM=powertrain control module ECM=engine control module EM=engine modification 2 (prefix)=parallel 2(suffix)=in series			C230/C230 {230hp}, CH230/CH230 (230hp), C250/C250 (250hp), CH250/CH250 (250hp)			

The following are the exhaust emission standards, or family emission limit(s) (FEL) as applicable, and certification levels for this engine family for hydrocarbons (HC) or non-methane hydrocarbons (NMHC), oxides of nitrogen (NOx), or NMHC+NOx, carbon monoxide (CO), particulate matter (PM), and formaldehyde (HCHO) in grams per brake horsepower-hour (g/bhp-hr) (Title 13, California Code of Regulations, (13 CCR) Section 1956.1 (urban bus) or 1956.8 (other than urban bus)): (The emission standards and certification levels for default operations permitted under 13 CCR Section 1956.1 or 1956.8 are in parentheses.)

* = not applicable [g/bhp-hr]	нс	NMHC	NOx	NMHC+NOx	co	PM	нсно
(DIRECT) STANDARD	1.3	•	*	*	15.5	0.10	*
CORPORATE AVERAGE STANDARD	•	•	4.0	*	*	•	•
FAMILY EMISSION LIMIT (FEL)	*	•	3.8	•	•	•	•
CERTIFICATION LEVEL	0.2	•	3.7	*	1.6	0.10	*

**BE IT FURTHER RESOLVED:** That certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR Sections 1965 (emission control labeling), and 2035 et seq. (emission control system warranty).

Engines certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-4-246 dated November 30, 2000.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division

## " mary Form Engine Model ?

PITHCHAMEN

International E. O. # A-4-246 Manufacturer:

On-highway HDDE Engine category:

1NVXH0466ANB EPA Engine Family. **DT 466 AND DT 466 HT** Mfr Family Name:

**New Submission** Process Code:

•	4 €			٧	A
9.Emission Control Device Per SAE J1930				CAC CAC DOI, ECM, TC, CAC	
9.Emission Control evice Per SAE J193	DI, ECM, TC,	DI, EEAR, TC,	61.0 ( ) DI, ECNY, TC, 74.5 ( ) DI, ECNY, TC,	F	- 437
ion (	Σ		<b>E S S S</b>	S 680	11 51 5 21 51 5
niss e Pe	. й	AT 1	<u>т</u> Ат	L A	
9.Er evic	급급	<u> </u>	ם ה	7	
e e				JAP.	
8.Fuel Rate: (lbs/hr)@peak torque	6		سد		
8.Fuel Rate: hr)@peak tor	Average 57.1	61.0	61.0 74.5		1-1
@ rel	. Ve	9	,9 .9		
8.I s/hr)			VIII J. J.		
<del>g</del> )					
ak a					株さす 月子/2
Rate @pe	verage 121.7	130.0	130.0 158.8		
7.Fuel Rate: n/stroke@pe torque	Average 121.7	3	13. 13.		
7.Fuel Rate: mm/stroke@peak torque					
٤					
-			. J		) (1344) (441)
6.Torque @ RPM (SEA Gross)	Advertised 620 @ 1400	660 @ 1400	660 @ 1400 800 @ 1400		
Forque @ RP (SEA Gross)	<u>=</u> (9)	(a) (	3) (B) (E)		
orqu	20.5	09	3 8		
6.Tc	7 0	9	တ ထ		
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)			E.S.		9145°
Rate peal ds or	verage 96.9	92.0	100.0 103.2		
5.Fuel Rate: s/hr) @ peak or diesels onl	Average 96.9	6			OFF.
5.Fuel Rate: lbs/hr) @ peak Hf (for diesels only)			#618* 		3441 1377 1 1877
_				1376 1437	
유(					
ate: peal only	ည်	4 (	Ω α		
el R e @ eset	\verage 125.8	0.00	3, 45		
4. Fuel Rate: n/stroke @ peak (fcr diesel only)	Average 125.8		129.8		CLASSIC CLASSIC CONTROL
4.Fuel Rate: mm/stroke @ peak HP (fcr diesel only)		14.54	i-la Ceda		
	1: 7: 4; 2: 7: 4; 4: 7: 41	Υŧ	Film Film		
∑ (§	- S	8	3 8		532
@R. Gros	rtise 3 23	23	23 23	es	
3.BHP@RPM (SAE Gross)	Advertised 230 @ 2300	0	၁ ဝ ရာ ရာ		
3.1	Advertised 230 @ 2300	23	25		
	: 10 				and the same of th
del					The second secon
Š		8	20		
jine	C230	H2.	3 2		
Eng	1 to 1	O	- 0	- 174	
2.		in die			
1.Engine Code 2.Engine Model	C230 C230	CH230 CH230 3300 119,4	CH250 CH250 250 @ 2300		を表現のできます。 のでは、これでは、これでは、これでは、これでは、これでは、これでは、これでは、これ
Coc		0	. 0		- 12 - 12
ine	C230	123	425 425		
Eng		ਹ ਪ	ت د		
=					
	** ** *			' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	4 T 4 M

ATTACHMENT

( det

at the second of the second of

: |

A-4-246-1

the second spin and the second second