CUMMINS INC.

EXECUTIVE ORDER A-021-0342-2 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board (ARB) by Health and Safety Code (HSC) Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order (EO) G-02-003; and

Pursuant to the December 15, 1998 Settlement Agreement (SA) between ARB and the manufacturer, and any modifications thereof to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZE (liter)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas; LPG≖liquefied petroleum gas)	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS (L/M/H HDD=light/medium/heavy heavy-duty [HD] diesel; UB=urban bus; HDO=HD Otto)			
2003	3CEXH0912XAH	14.9	Diesel	Diesel	HHDD			
	AL FEATURES & CONTROL SYSTEMS		ENGINE MODELS / CODES	(rated power in h	orsepower, hp)			
DDI, TO	C, CAC, PĊM, EGR		See At	ttachments ·				
GVWR=gros	s vehicle weight rating T	NC/OC=three-	wayloyidizing catalyet Will (profix) marming cot	025-0	LIAAS L			

GVWR=gross vehicle weight rating TWC/OC=three-way/oxidizing catalyst WU (preflx) =warm-up cat. O2S=oxygen sensor HO2S=heated O2S TBI=throttle body fuel injection MFI=multi port fuel injection SFI=sequentialMFI DDI/IDI=direct/indirect diesel injection TC/SC=turbo/super charger CAC=charge air cooler EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR SPL=smoke puff limiter ECMPCM=engine /powertrain control module EM=engine modification 2 (preflx)=parallel (2) (suffix)=in series HC=hydrocarbon NMHC=non-methane HC NOx=oxides of nitrogen CO=carbon monoxide PM=particulate matter

The following are the exhaust emission standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT), in g/bhp-hr, for this engine family under the "Federal Test Procedure" (FTP) (Title 13, California Code of Regulations, (13 CCR) Section 1956.1 (urban bus) or 1956.8 (other than urban bus)), and under the "Euro III Test Procedure" (EURO) in the Settlement Agreement, including EURO's "Not-to-Exceed" standard(s). "Diesel" CO certification compliance may have been demonstrated pursuant to Code of Federal Regulations, Title 40, Part 86, Subpart A, Section 86.091-23(c)(2)(i) in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR Section 1956.1 or 1956.8 are in parentheses.)

			EURO'	S NOT-TO	-EXCEE	STD	NMHC: 0	.625	NOx: *		NMHC+NC	Ox: 3.0	PM: 0.125	
* = not	HC		NMHC		NOx		NMHC+NOx		СО		PM		. нсно	
applicable	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURC	FTP	EURO	FTP	EURO
(DIRECT) STD	*	*	0.5	0.5	*	*	*	•	15.5	15.5	0.10	0.10	٠	*
AVERAGE STD	*	*	٠	•	*	*	2.5	*			+		*	+
FEL	*	•	*	•	*	*	2.4	2.4	*	*	•	•	•	+
CERT	*	*	0.1	0.05	•	•	. 2.2	1.9	1.0	0.4	0.08	0.07	*	•

BE IT FURTHER RESOLVED: That certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR Sections 1965 (emission control labels), and 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: That the listed engine models are conditionally certified subject to the following conditions: (1) The SA is in effect; (2) The manufacturer is in compliance with all applicable California emission regulations, and all SA's applicable requirements and any modifications thereof; and (3) The manufacturer has elected to seek certification of the listed engine models under the SA's provisions in Chapter VI.E (Averaging, Banking and Trading) and shall be required to comply with these and any other related provisions.

Engines certified under this Executive Order shall conform to all applicable California emission regulations and all requirements under the Settlement Agreement and any modifications thereof.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2003.

Allen Lyons, Chief Mobile Source Operations Division

Engine Model S'''mmary Form

Cummins Inc. Manufacturer:

Engine category: On-highway HDDE

EPA Engine Family: 3CEXH0912XAH

Mfr Family Name: 103H
Process Code: Running Change

A-021-0342-2

	¥.	A +1-	۵۷	2~~	عبه	1 ४५	<u>ع</u>					F	\	221	- Ô	34	- ユ-	9
9.Emission Control Device Per SAE J1930	POM, EGR, TO	POM EGE TO	PCM, EGB, TO,	POM, EGR, TO	POM/EGE, TO	PCM, EGR, TC. PCM FGB TC	PCM, EGR, TC.	PCM, EGB, TC.	POM, EGR, TC, POM, EGR TC	PCM, EGR, TC.	POM, EGR, TOLV	POMIEGRATOL	PCM, EGR, TC.	PCM EGR TO	PCM, EGR, TO	PCM, EGR, TC.	POM, EGR, TC,	POMJEGRI, TO POMJEGRI, TC.
8. Fuel Rate: (lbs/hr)@peak torque	150 DD	129	129	129	129	129	118	129	118	129	ት 011	(99)	129	129	129	150	129	7.18 25 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
7.Fuel Rate: mm/stroke@peak torque	371	320	320	320 :- 371	320	320 1 320	291	320	273 1	320	474	971	320	320	320	37.1	320	291
6.Torque @ RPM (SEA Gross)	1850@1200 1650@1200	1650@1200	1650@1200	1850@1200	1650@1200	1650@1200	1550@1200	1650@1200 1550@1200	1450@1200	1650@1200 1450@1400	* Indagada	1850@1200	1650@1200 1650@1200	1650@1200	1650@1200 ***	1650@1200	1659@1200	1550@1200
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	197	197	261	185	185	162	162	46	146	162	7.0	197	197	197	197	185	185	162
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	325	325	325	304	304 304	266	266	241	24.241	266		325	325	7425 dor	904	304	304 266	266
3.BHP@RPM (SAE Gross) 525@1800	525@1800	525@1800 525@1800	525@1800	500@1800	500@1800 500@1800	464@1800 +	404(@1800 425(@1800	425@1800	425@1800 464@4800		out strong	525@1800 525@1800	525@1860	525@1800 525@1800	500@+800	500@1800	aut@ 800 464@1800	464@1800
2.Engine Model	15X 500	SX 525	1 SX 525 L	ISX 475	SX 475ST	15X 450 1	Ex400	ISX 400	ISX 4657	(SX 325V	BY FOO.	(SX 500	SX 500ST	ISX 525	ISX 475	SX 475 + SX 4763T	ISXA60, II.	ISX 450
1.Engine Code 8285;FR10481	82851FR10480 82851FR10489	8285;FR10485	8285JFF1 0486	8285;FF10478 8285;EF10477	8285;FR10479	8285/FR10476	8285/FF10471	82857FR10470	8285/FP10492	8285FR10493	BENERAL BERRITARY	8286;FR10480	82861FB10482 11	ozabjari 1485 8286/FRT 10486	8286;FR10478	8286/FET(1477 8286/FET(1479	8286 FF10475	8286;FR10474
<u> </u>			×	*		У.		* ;	4					-				

Engine Mode Jummary Form

Manufacturer: Cummins, Inc.

Engine category: On-highway HDDE EPA Engine Family: 3CEXH0912XAH

Mfr Family Name: 103H

Process Code: New Submission

A- 241-0342-3

9.Emission Control Device Per SAE J1930 P.P.C.M., EGR., T.C., P.C.M., EGR., T.C., P.C.
8.Fuel Rate: (lbs/hv)@peak torque 157 DD) 137 137 120 120 120
7.Fuel Rate: mnvstroke@peak torque 388 337 337 337 337 337 296 296 296 296
6. Torque @ RPM (SEA Gross) 1850@1200 1650@1200 1650@1200 1650@1200 1650@1200 1450@1200 1450@1200
5. Fuel Rate: (lisshu) @ peak Hp (for diesels only) 204 204 204 191 170 170 154 154
4.Fuel Pate: mm/stroke @ poak P (for diesel ouly) 337 337 315 280 280 254 254 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2554 2555 25
3.BHP@RPM (SAE Gross) 525@1800 525@1800 525@1800 464@1800 464@1800 425@1800 425@1800
2.Engine Model ISX 500 ISX 500ST2 ISX 500 ISX 475 ISX 450ST2 ISX 450ST2 ISX 400 ISX 400ST2
1.Engine Code 8259;FR10427 8259;FR10425 8259;FR10421 8259;FR10419 8259;FR10416 8259;FR10416 8259;FR10416