	رهم	,orn	48 C.A	тони	16 M	el m	ween	юял	ugenicy			
	A	D	DE	:0/	11	D		C	DC	A	DI	
-	~	n	nc	30	"	יחי		3	DU	-	nı	9

DAIMLERCHRYSLER AG

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC) Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZE (liter)	FUEL TYPE {CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas}	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS {L/WH HDD=light/medium/heavy heavy-duty [HD] diesel; UB=urban bus; HDO=HD Otto)
2004	4MBXH6.37DJA	6.37	Diesel	Diesel MHDD	
	IAL FEATURES & CONTROL SYSTEMS		ENGINE MODELS / CODES		
DDI, TO	C, CAC, ECM, EGR		OM 906LA / I (260 hp), OM 906LA OM 906LA / IV (210 hp), OM 906L	A / II (250 hp), OM A / V (210 hp), OM	906LA / III (230 hp), 906LA / VI (190 hp),
TWC/OC=th	ree-way/oxidizing catalyst	WU (prefix) =\	warm-up cat. O2S=ðxygen sensor HO2S=heated	O2S TBI=throttle bo	dy fuel injection MFI=multi port fuel injection

SFI=sequentialMFI DDI/IDI=direct /Indirect diesel injection TC/SC=turbo/super charger CAC=charge air cooler EGR=exhaust gas recirculation AlfR=secondary air injection PAIR=pulsed AIR SPL=smoke pufi limiter ECM/PCM=engine /powertrain control module EM=engine modification 2 (prefix)=parallel (2) (suffix)=in series

The following are the exhaust emission standards (CERT), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) in grams per brake horsepower-hour (g/bhp-hr) for this engine family for hydrocarbon (HC) or non-methane HC (NMHC), oxides of nitrogen (NOx), or NMHC+NOx, carbon monoxide (CO) [except that "diesel" CO certification compliance may have been demonstrated pursuant to Code of Federal Regulations, Title 40, Part 86, Subpart A, Section 86.091-23(c)(2)(i) in lieu of testing], particulate matter (PM), and formaldehyde (HCHO) under the "Federal Test Procedure" (FTP) (Title 13, California Code of Regulations, (13 CCR) Section 1956.1 (urban bus) or 1956.8 (other than urban bus)): (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR Section 1956.1 or 1956.8 are in parentheses.)

* = not applicable [g/bhp-hr]	HC	NMHC	NOx	NMHC+NOx	co	PM	нсно
(DIRECT) STANDARD	*	0.5	•	2.5	15.5	0.10	*
CORPORATE AVERAGE STANDARD	*	*			7.	*	*
FAMILY EMISSION LIMIT (FEL)	*	*	•		+	*	*
CERTIFICATION LEVEL	*	0.1		2.4	1.4	0.10	*

BE IT FURTHER RESOLVED: That certification to the **FEL(s)** listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR Sections 1965 (emission control labels), and 2035 et seq. (emission control warranty).

Engines certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order is not valid for engines produced on or after February 1, 2004.

Executed at El Monte, California on this 15th day of January 2004.

Allep Lyons, Chief Mobile Source Operations Division