Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE '	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS <sup>2</sup>	ECS & SPECIAL FEATURES 3
2005	5CEXH0912XAH	14.9	Diesel	Diesel	HHDD	PCM, EGR, DDI, TC, CAC
ENGINE (L)			ENGINE N	MODELS / CODES (ra	ated power, in	
14.9				See Attachme	nt	
*				*		
*				*		
*				*		86.abc=Tille 40, Code of Federal Regulations, Section 86.abc;

L=iller; np=horsepower; kw=kilowalt;
CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;
L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDD=heavy duty Otto;
ECS=emission control system; TWC/DC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO25/O25=heated/oxygen sensor; HAFS/F fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGT=direct gasoline injection; GCARB=gase; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; : HAFS/AFS (2004may26)

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NI	NMHC		Ox	NMH	C+NOx	C	0		РМ	нсно		
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	
STD	0.5	0.5	*	*	2,5	2.5	15.5	15.5	0.10	0.10	*	*	
FEL	*	ŵ	*	*	*	•			· ·	*	*		
CERT	0.2	0.1	*	*	2.3	1.9	1.0	0.4	0.09	0.07	*	*	
NTE	0.	625		*	3.	125	19.	375		125	<del>                                     </del>		

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed; STD=standard or emission test cap; L=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldel

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

day of December 2004.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Mobile Source Operations Division

## Engine Model S nmary Form

Attachmont: List of Engine Model e Code

Anufacturer: Cummins Inc.
Engine category: On-highway HDDE

PA Engine Family: 5CEXH0912XAH

Mir Family Name: 103H

Process Code: New **Su**bmis**sion** 

1.Engine Code 2.1 8259;FR10427 8259;FR10425 8259;FR10422 8259;FR10421 8259;FR10419 II 8259;FR10418		3.BHP@RPM	4.Fuel Hate: mm/stroke @ peak HP	o.ruei Hate: (lbs/hr) @ peak HP	6.Torque @ RPM	7.Fuel Rate: mm/stroke@peak	8.Fuel Rate:	9.Emission Control
	Z.Engine Model	(SAE Gross) 525(@1800	(for diesel only)	(for diesels only)	(SEA Gross) 1RED <i>i</i> คตาวกก	torque 388	(lbs/hr)@peak torque	ے ت
	SX 500ST2	525@1800	337	204	1650@1200	337	7	PCM
	ISX 500	525@1800	337	204	1650@1200	337	137	EGR.
	ISX 475	500@1800	315	191	1650@1200	337	137	PCM, EGR, TG,
	ISX 450	464@1800	280	170	1650@1200	337	137	
-R10418	SX 450ST2	464@1800	280	170	1450@1200	296	120	PCM, EGR, TC,
	ISX 400	425@1800	254	154	1650@1200	337	137	PCM, EGR, TG,
8259;FR10416	SX 400ST2	425@1800	254	154	1450@1200	296	120	PCM, EGR, TC,
8259;FR10415	ISX 400	425@1800	254	154	1450@1200	296	120	PCM, EGR, TC,
8285;FR10481	ISX 500	525@1800	325	197	1850@1200	37.1	150	PCM, EGR, TC,
8285;FR10480	ISX 500	525@1800	325	187	1650@1200	320	129	PCM, EGR, TC,
8285;FR10482	ISX 500ST	525@1800	325	197	1650@1200	320	129	PCM, EGR, TC,
8285;FR10485	ISX 525	525@1800	325	197	1650@1200	320	129	PCM, EGR, TC,
8285;FR10486	ISX 525	525@1800	325	197	1650@1200	320	129	PCM, EGR, TC,
8285;FR10478	ISX 475	500@1800	304	185	1850@1200	371	150	PCM, EGR, TC,
8285;FR10477	ISX 475	500@1800	304	185	1650@1200	320	129	PCM, EGR, TC,
8285;FR10479	ISX 475ST	500@1800	304	185	1650@1200	320	129	PCM, EGR, TC,
8285;FR10475	ISX 450	464@1800	266	162	1650@1200	320	129	PCM, EGR, TC,
8285;FR10474	ISX 450	464@1800	266	162	1550@1200	1,291	118	PCM, EGR, TC,
8285;FR10471	ISX 400	425@1800	241	146	1650@1200	320	129	PCM, EGR, TC,
8285;FR10470	ISX 400	425@1800	241	146	1550@1200	291	118	PCM, EGR, TG,
8285;FR10469	ISX 400	425@1800	241	146	1450@1200	273	110	PCM, EGR, TC,
8285;FR10492	ISX 465V	464@1800	266	162	1650@1200	320	129	PCM, EGR, TC,
8285;FR10493	ISX 325V	425@1800	241	146	1450@1200	273	110	PCM, EGR, TC,
8283;FR10484	ISX 565	590@1800	349	212	1850@1200	37.1	150	PCM, EGR, TC,
8283;FR10483	ISX 530	550@1800	328	199	1850@1200	371	150	PCM, EGR, TC,
8283;FR10481	ISX 500	525@1800	315	191	1850@1200	371	150	PCM, EGR, TC,

EGR, TC, CAC	ЕСН, ІС,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,	EGR, TC,
\$56069	۳ لار		PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PCM, E	PGM, E	PCM, E	PCM, E	PCM, E	U PCM, E
	061	132	132	132	132	150	150	145	132	132	145	145	145	132	132	145	132	132
327	97.1	327	327	327	327	370	370	358	327	327	358	358	358	327	327	358	327	327
650@1200 850@1200	550@1200 550.	65U@1ZUU	650@1200	650@1200	650@1200	850@1200	850@1200	850@1200	650@1200	650@1200	850@1200	850@1200	850@1200	650@1200	650@1200	850@1200	650@1200	650@1200
				*	191	216	216	217	-	197	212	203	197	197	197	187	187	187
5	ר ע	0 1	5	Ð	5	5	5	7	5	5	0	5	5	5	5	æ	8	8
315	063	D C	295	315	315	355	355	357	325	325	350	335	325	925	325	308	308	308
525@1800 500@1800	500@1000	TOOLIGIE	500@1800	0081002c	525@1800	600@1800	600@1800	600@1800	525@1800	525@1800	590@1800	550@1800	525@1800	525@180 <b>0</b>	525@1800	500@1800	500@1800	500@1800
SX 500ST ISX 475	0.1+ X0.1 10 X X 7.1	107 470	157,47551	<b>3</b> 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	(SX 525	18×600	18× 600	(SX 600	ISX 525	SX 525	ISX 565	ISX 530	ISX 500	ISX 500	ISX 500ST	ISX 475	ISX 475	ISX 47551
283;FR10/*** 283:FR104	283;FHT04: 3			Z83,FH10483	3283;FH1048b	283;FR10507	3283;FR10508	3518;FR10507	518;FR10485	3518;FR10486	8518;FR10484	8518;FR10483	8519;FH10481	8519;FR10480	8519;FH10482	8519;FH10478	8519;FR10477	8519;FH10479