

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1269 New Engines for Diesel or Incomplete Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in diesel or incomplete medium-duty vehicles with a manufacturer's GVWR from 8501 to 14000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	EMISSION STD CATEGORY 2	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	ENGINE SIZES (L)	ECS & SPECIAL FEATURE	s ³	OBD COMPLIANCE	
2005	5FMXH06.8TH5	ULEV	Gasoline	Otto	6.8	TWC, 2HO2S, HO2S, S	FI	OBD(P)	
	ENGINE (L)	OBD COMPLIANCE							
	6.8	OBD(P)							
	•	*							
	•	*							
' =not appli	cable: GVWR=gross vehic	la weight rating: 42 (	* * * * * * * * * * * * * * * * * * *	7		D 86 about 10 Oct 15	*	*	

e of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; (2004may26) Interpolations (GWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Recompressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a BF=bi fuel; DF=dual fuel; FF=flexible fuel; SULEV / ULEV / LEV=super ultra / ultra / low emission vehicle; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sections and the superior of the super

SOLEY / LEY - Super unitar / undar / sw emission vernice,

ECS-emission control system: TWC/OC=three-way/oxidizing catalyst; WU (preftx) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=>
fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; OGI=direct gasoline injection; GCARB=gaseous clip/IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff IOBD(F) / (P) / (S)=full / partial / partial

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For dual- and flexible-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel.)

NMHC		NOx		NMHC+NOx		со		PM		нсно	
FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO		EURO
_ •	•	*	*	1.5	*	14.4	*	*			
*	*	*	•	*	•	*	•	*	+	•	
•	•	+	*	0.6	•	2.9	<del>                                     </del>		+	0.003	
	•		•		*						<u> </u>
					FTP EURO FTP EURO FTP  1.5  1.5	FTP EURO FTP EURO FTP EURO  1.5  1.5  1.5	FTP EURO FTP EURO FTP EURO FTP  1.5 14.4	FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO	FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP </td <td>FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO  1.5 1.5 14.4 1 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1</td> <td>FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         O.050  .</td>	FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO  1.5 1.5 14.4 1 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1	FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         EURO         FTP         O.050  .

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the optional emission standards and test procedures in 13 CCR 1956.8 applicable to diesel or incomplete medium-duty vehicles with a GVWR from 8501 to 14000 pounds and, therefore, shall be subject to 13 CCR 2139(c) (in-use testing of engines certified for use in diesel or incomplete medium-duty vehicles with a 8501-14000 pound GVWR).

**BE IT FURTHER RESOLVED:** The listed engine models have been certified to the Option 1 federal NMHC+NOx emission standard listed above pursuant to 13 CCR 1956.8.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1968.2 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of July 2004.

Allen Lyons, Chief Mobile Source Operations Division