Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

						g
MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	SERVICE CLASS ²	ECS & SPECIAL FEATURES 3
2007	7CEXH0912XAL	14.9	Diesel	Diesel	HHDD	DDI ECHINE CAR SEE
ENGINE (I	L)		ENGINE MO	DELS / CODES (r		DDI, ECM, TC, CAC, EGR, OC, PTOX
14.9				SEE ATTACHEM	/ENT	
*				*		
*				*		
=not applic	cable; GVWR=gross vehicl	e weight rating: 13 CCA	IVZ=Title 13 California Code	*		

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86 abc; liter, hp=horsepower, kw=kilowatt,

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=duel fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus, HDO=heavy duty Otto;

DM/H HDF-light/medium/neavy neavy-duty diesel, Ub-urdain bus, HDF-neavy duty Otto,

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF-diesel particulate filter, PTOX= Periodic Trap Oxidizer; HO2S/O2S=heated/oxygen sensor; TSFIxMFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TSFIxMFI=sequential/mith port fuel injection; DGF-direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbols-uper charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; (2007Jan06)

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible and stall fueled angles, the CERT values in breakets I lead these when tested on applicable test field. For multi-finited of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

FTP		·			NMHC+NOx		7 00							
	EURO	FTP EURO				CO		РМ		нсно				
0.14			EURU	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO			
*	0.14			_ * _	*	15.5	15.5	0.01	0.01	*	•			
0.00				1.2	1.2	*	*	*	*	*				
				1.2	0.9	1.0	0.1	0.01	0.001	*	*			
1.8			19.375		0.015		*							
on limit; C	ERT=certific		Federal Tes NMHC/HC=r	it Procedure; I non-methane/hy	EURO=Euro III /drocarbon; N	European Stea	dy-State Cycle;	NTE≃Not-to-	-Exceed STD=					
(per brake n limit; C	0.00 0.00 0.21 s per brake horsepower n limit; CERT=certific	1.20 0.00 0.00 1.19 0.21 1.8 s per brake horsepower-hour, FTP- n limit; CERT=certification level;	* * 1.20 1.20 0.00 0.00 1.19 0.90 0.21 1.80 s per brake horsepower-hour, FTP=Federal Tes	1.20 1.20 1.2 1.00 0.00 1.19 0.90 1.2 1.20 1.20 1.20	* 1.20 1.20 1.2 1.2 0.00 0.00 1.19 0.90 1.2 0.9 0.21 1.8 s per brake horsepower-hour, FTP=Federal Test Procedure, EURO=Euro III in limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; N	15.5 1.20 1.20 1.20 1.2 1.2 1.0 1.0 1.0	* 1.20 1.20 1.2 1.2 1.2 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	15.5 15.5 0.01	1.14 0.14 * * * * * * * * * * * * * * * * * * *	1.14 0.14 * * * * 15.5 15.5 0.01 0.01 * * * * * 1.20 1.20 1.2 1.2 * * * * * * * * * * * * * * * * * * *			

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of January 2007.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: Cummins Inc.

Engine category: On-highway HDDE

EPA Engine Family. 7CEXH0912XAL Mfr Family Name: 103L

Process Code: New Submission

9.Emission Control ue Device Per SAE J1930	DUI PTOX, FCM,	TC, RTOX, PCM,	Э.К., РТОХ, РФМ,	GGI(, PTOX, PCM,	DC PTOX, PCM.	PTOX\PCM,	PTOX/PCM,	PTOX, PCM,	PTOX, PCM,	РТФХ, РФМ,	PJÓX, PCM,	PTOX, PCM,
8.Fuel Rate: (lbs/hr)@peak torque	149\ ¬	149	132 (149	149	132	139	132	120	139	149	132 /
7.Fuel Rate: mm/stroke@peak torque	367	367	326	367	367	326	342	326	298	342	367	326
6.Torque @ RPM (SEA Gross)	1850@1200	1850@1200	1020(@1200	1850@1200	1850@1200	1650@1200	1750@1200	1650@1200	1550@1200	1750@1200	1850(@1200	00717000
5.Fu (lbs/hr) (for die	193	102	191	101	101	101	102	162	102	107	184	
4,Fuel Rate: mm/stroke @ peak HP (for diesei only)	318 318	318	299	299	299	787	267	267	267	299	299	wer the same of th
3.BHP@RPM (SAE Gross)	525@1800	525@1800	500@1800	500@1800	500@1800	450@1800	450@1800	450@1800	450@1800	500@1800	500@1800	
2.Engine Model	ISX 500ST	ISX 500	ISX 485ST	ISX 485	ISX 485	ISX 450ST	ISX 450	ISX 450	ISX 450ST	ISX 500V	ISX 500V	
1.Engine Code 1434;FR10637	1434;FR10636	1434;FR10638	1434;FR10639	1434;FR10640	1434;FR10641	1434;FR10642	1434;FR10644	1434;FR10645	1434;FR10643	1434;FR10634	1434;FR10635	

A-021-0444

ATTACHMENT