EXECUTIVE ORDER A-021-0508
New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	AR ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
2008			8.9	CNG / LNG	PROCEDURE	CLASS T	TBI, TC, CAC, EGR, ECM, TWC, HO2S					
1	'ENGINE'S IDLE NS CONTROL			AD	DITIONAL IDLE EN		E	<u> </u>				
E	xempt			*.···	N	/A						
ENGINE (L	L)			ENGINE MO	DELS / CODES (rai	ted nower in	hn)					
8.9	ISL G 320 / 3	ISL G 320 / 3297;FR92882 (320); ISL G 300 / 3297;FR92883 (300); ISL G 280 / 3297;FR92884 (280); ISL G 260 / 3297;FR92885 (260 ISL G 250 / 3297;FR92886 (250)										
	<u> </u>											
	-	-		······································		·						
* =not applic	cable: GVWR=gross	vehicle w	eight rating: 13 CCR	vvz=Title 13 California Code	of Pagulations, Coat	46.055	R 86.abc=Title 40, Code of Federal Regulations					
CNG/LN  LIM/H H  ECS=em  up catalyst; TBI=throttie super charge	IG=compressed/lique IDD=light/medium/he nission control system DPF=diesel particul body fuel injection ler: CAC=charge air	efied natur avy heavy n; TWC/C ate filter; SFI/MFI=: cooler: E	al gas; LPG=liquefied -duty diesel; UB=urb; DC=three-wayloxidizing PTOX=periodic trap to sequential/multi port to	Petroleum gas; E85=85% e an bus; HDO=heavy duty Ot g catalyst; NAC=NOx adsory kidizer; HO2S/O2S=heated/ et injection; DGI=direct gass.	thanol fuel; MF=multi to; otion catalyst; SCR-U xygen sensor; HAFS	fuel a.k.a. BF: / SCR-N=selection	** doi.abc=1 rile 40, Code of Federal Regulations  =bi fuel; DF=dual fuel; FF=flexible fuel;  tive calalytic reduction urea / ammonia; Will  air-fuel-ratio sensor (a.k.a., universal or linear or  buretor; IDM/DDI=indirect/direct dieset injection;  injection; SPL=smoke puff limiter; ECM/PCM=	U (prefix) =warm- rygen sensor);				
<sup>5</sup> ESS≔eng (per 13 CCR	gine shutdown system R 1956.8(a)(6)(D); Ex	m (per 13 <b>xempt</b> =ex	CCR 1956.8(a)(6)(A)( empted per 13 CCR 1	1): 30 m = 30 m/hr NOv (nor 13	CCR 1956.8(a)(6)(C)	; APS =interna	al combustion auxiliary power system; ALT≖atte (e.g., Otto engines and vehicles);					

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	- t
FEL	*	*	*	*	*	* .	*	*	*	0.01 *		<u> </u>
CERT	0.13	0.04	0.10	0.01	*	•	1.2	0.4	0.01	0.00	*	*
NTE	0.21		0.30			*		9.4	0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of March 2009.

Annette Hebert, Chief

Mobile Source Operations Division