Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		ENGINE	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC ON N/A				
TEAR			SIZES (L)	~~· ***·	PROCEDURE	CLASS 2	TBI, TC, CAC, EGR, ECM, TWC,					
2009 9CEXH05		LBE	8.8	CNG / LNG	Diesel	HHDD	HO2S					
	ENGINE'S IDLE ONS CONTROL			AD	DITIONAL IDLE EN	lissions co	NTROL 5					
E	Exempt	N/A										
ENGINE ((L)			ENGINE MO	DELS / CODES (ra	ted power, in	hp)					
8.8	ISL G 320 /	ISL G 320 / 3297;FR92882 (320); ISL G 300 / 3297;FR92883 (300); ISL G 280 / 3297;FR92884 (280); ISL G 260 / 3297;FR92885 (260)										
				<u> </u>								
and and	imble: GVM/P-gross	vobiclo	wight rating: 12 CCC	www.Title 12 California Cad	a of Bassilations, Saal	40.05	R 86.abc=Title 40, Code of Federal Regulation	- C-+ 00 - b				
.=liter; hp	=horsepower; kw≂ki	lowatt; hi	≠nour;		•	-	•	is, Section 85.abc;				
						ti fuel a.k.a. BF	=bi fuel; DF≌dual fuel; FF≂flexible fuel;					
				oan bus; HDO=heavy duty O			-K					
p catalyst;	; DPF=diesel particu	late filter;	PTOX=periodic trap	oxidizer: HO2S/Q2S=heated/	oxygen sensor: HAF	S/AFS=heated/	ctive catalytic reduction – urea / – ammonia; V air-fuel-ratio sensor (a.k.a., universal or (inear (oxvoen sensor):				
'Bl≃throitle uper char	e body fuel injection; ger; CAC≃charge air	SFVMFI= cooler: E	sequential/multi port t :GR / EGR-C=exhaus	uel injection; DGI≖direct gas: t gas recirculation / cooled E0	oline injection; GCAR GR: PAIR/AIR≃oulser	B=gaseous car d/secondary air	buretor; IDVDDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM	r; TC/SC≕turbo/ ≕encine/nowedrai:				
ontrol mod	dule; EM≂engine mo	dification;	<pre>2 (prefix)=parallel;</pre>	(2) (suffix)=in series;	·	•						
ESS=er per 13 CC	ngine shuldown syste R 1956.8(a)(6)(D); E	m (per 13 xempt≃e:	I CCR 1956.8(a)(6)(A xempted per 13 CCR)(1); 30g=30 g/hr NOx (per 1: 1956.8(a)(6)(B) or for CNG/Li	3 CCR 1956.8(a)(6)(C NG fuel systems; N/A	:); APS =intern =not applicable	al combustion auxiliary power system; ALT=ale (e.g., Otto engines and vehicles);	ternative method				
				1): OBD=on-board diagnosti			• • •					

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	
FEL	*	*	,	*	*	*	*	*	*	*	*	*
CERT	0.13	0.04	0.11	0.01	*	*	1.2	0.4	0.01	0.001	+	*
NTE	0.21		0.30		*		19.4		0.02		*	

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

This Executive Order hereby cancels Executive Order A-021-0478, dated June 3, 2008.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of June 2008.

Annette Hebert, Chief

Mobile Source Operations Division