**EXECUTIVE ORDER A-021-0484-1** New On-Road Heavy-Duty Engines Page 1 of 2 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
YEAR ENGINE FA		SIZES (L)			PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,	EMD				
2009	9CEXH0661	EXH0661MAE 10.8		Diesel	Diesel	HHDD	PTOX	LIVID				
	' ENGINE'S IDLE NS CONTROL		ADDITIONAL IDLE EMISSIONS CONTROL 5									
	30g		N/A									
ENGINE (	L)	ENGINE MODELS / CODES (rated power, in hp)										
10.8		See attachment for engine models and ratings										
*	CINED.		-i-bidi 49 CC	D	f Desiries - Com	40 CE	P. P. aba-Title 40. Code of Federal Populations	Costion PC aba:				

\*=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst, SCR-U / SCR-N=selective catalytic reduction – urea / -- ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI+throttle body fuel injection; SFVMFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diésel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		со		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	+	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	1.95	1.95	1.9	1.9	. *	*	*	*	*	+
CERT	0.04	0.01	1.69	1.61	1.68	1.62	0.35	0.02	0.002	0.002	*	*
NTE	0.21		2.44		2.4		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methana/hydrocarbon; NOx=oxides of nitrogen CO=carbon monoxide; PM=particulate matter, HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

EXECUTIVE ORDER A-021-0484-1 New On-Road Heavy-Duty Engines Page 2 of 2 Pages

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-021-0484 dated February 3, 2009.

Executed at El Monte, California on this day of March 2009.

Annette Hebert, Chief Mobile Source Operations Division

## **Engine Model Summary Template**

Attachan ent A-021-0484-1

	ē											
8.Fuel Rate: 9.Emission Control (Ibs/hr)@peak torqueDevice Per SAE J1930	$\rho$ PTOX, PCM,	PYOX, PCM,	Ртох, РСм,	PTOX, PCM,	/ PTOX/PCM,	PTOX/PCM,	PTOX, RCM,	PTOX, PCM,	Ртрх, Рфм,	PTOX, PCM,	PTOX, PCM,	C PTOX, PCM.
8.Fuel Rate: (lbs/hr)@peak torqı	119	111	11	102	119	11	119	==	119	111	119	÷
7. Fuel Rate: mm/stroke@peak torque	294	274	274	252	294	274	294	274	294	274	294	274
6.Torque @ RPM (SEA Gross)	1450@1200	1350@1200	1350@1200	1250@1200	1450@1200	1350@1200	1450@1200	1350@1200	1450@1200	1350@1200	1450@1200	1350@1200
5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	141	141	134	134	141	130	141	141	130	130	141	134
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	232	232	221	221	232	214	232	232	214	214	232	221
3.BHP@RPM (SAE Gross)	385@1800	385@1800	365@1800	365@1800	385@1800	350@1800	385@1800	385@1800	350@1800	350@1800	385@1800	365@1800
2.Engine Model	ISM 370	ISM 370	ISM 350	ISM 350	ISM 350ST	ISM 330	ISM:385V	ISM 385V	ISM 350V	ISM 350V	ISM 385	, ISM 365
1.Engine Code 2.Engine Model	3281;FR20195	3281:FR20196	3281.FR20198	3281:FR20199	3281;FR20197	3281:FR20200	3281;FR20201	3281;FR20202	3281;FR20203	3281.FR20204	3281:FR20205	3281;FR20127
27 27 28 28 28			· -	N <sub>1</sub>		7 7 10	- 3					i

001, 7c, 040, ECM EGG, 06, PTDX