

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMIL	ENGINE	FUEL TYPE 1	STANDARDS & TEST	SERVICE 2	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
YEAR	00571100407	SIZES (L)	Diesel	PROCEDURE	CLASS HHDD	DDI, TC, CAC, ECM, EGR, OC, PTOX	EMD			
2009	9 9CEXH0912XAN 14.9		Diesei	Diesei	THIDD					
PRIMARY ENGINE'S IDLE ADDITIONAL IDLE EMISSIONS CONTROL 5  EMISSIONS CONTROL										
30g		N/A								
ENGINE (L)				ENGINE MODELS / CODES (rated power, in hp)						
14.9	14.9 ISX 600 / 3320;FR10784 (615), ISX 600 / 3320;FR10783 (615), ISX 550 / 3320;FR10782 (578), ISX 525 / 3320;FR10781 (550) ISX 600 / 3320;FR10788 (600), ISX 525 / 3320;FR10878 (525)  =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.at									
L=liter; hp=ho CNG/LNG L/M/H HD ECS=emis up catalyst; D TBI=throttle b super charger control modul	iorsepower; kw=kilon i=compressed/liquefi iD=light/medium/heav isight/medium/heav ippF=diesel particulati pody fuel injection; Si ir; CAC=charge air ci le; EM=engine modifi	watt, hr=hour; ed natural gas; LPG=lique y heavy-duty diesel; UB=1 TWC/OC=three-way/oxidi e filter; PTOX=periodic tra F/MFI=sequential/multi po pooler; EGR / EGR - C=exha fication; 2 (prefix)=parallel (Jan 13 - OR 1958 (20)6)	fied petroleum gas; E85=85% eth urban bus; HDO=heavy duty Otto izing catalyst; NAC=NOx adsorpti p oxidizer; HO2S/O28=heated/ox rt fuel injection; DGI=direct gasoli ust gas recirculation / cooled EGF - (2) (au/BI)=in series.	anol fuel; MF=mul; on catalyst; SCR-t ygen sensor; HAF ne injection; GCAF ; PAIR/AIR=pulse	ti fuel a.k.a. BF  J / SCR-N=sele SIAFS=heated/ RB=gaseous ca d/secondaty air  Ch APS =intern	bi fuel; DF=dual fuel; FF=flexible fuel;  ctive catalytic reduction – urea / – ammonia; Wair-fuel-railo sensor (a.k.a., universal or linear or fouretor. [DWDD]=indirect/direct diesel injection; SPL=smoke puff limiter; ECMPCM	VU (prefix) =warm- oxygen sensor); i; TC/SC=turbo/ =engine/powertrain			

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

in	NMHC		NOx		NMHC+NOx		co		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14				*	15.5	15.5	0.01	0.01	*	*
FEL	*		1.95	1.95	1.9	1.9	*	*	*	*	*	*
CERT	0.00	0.00	1.72	1.56	1.7	1.6	0.09	0.00	0.001	0.003	*	*
NTE	0.21		2.44		2.4		19.4		0.02		•	

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET≖ram mode cycle supplemental emissions testing; NTE=Nof-to-Exceed; STD=standard or emission test cap: FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

EXECUTIVE ORDER A-021-0507 New On-Road Heavy-Duty Engines Page 2 of 2 Pages

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of May 2009.

Annette Hebert, Chief Mobile Source Operations Division