Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES	EMD			
YEAR	Errointe i Ain	EMOUNT VINE			PROCEDURE	CLASS	DDI, TC(2), CAC, ECM, EGR,				
2009	9NVXH0757/	VXH0757AGA 12.3		Diesel	Diesel	HHDD	OC, PTOX				
	Y ENGINE'S IDLE ONS CONTROL			ADD	TIONAL IDLE EN	USSIONS CO	NTROL ⁵				
	ESS	N/A.									
ENGINE	(L)			ENGINE MODE	LS / CODES (ra	ted power, in	hp)				
12.3			GD	T475 / GDT475 (475), G	DT430 / GDT4	30 (4 30), G	DT410 / 410 (410)				
*					+						
L=liter; fig CNG/L ² L/M/H 3 ECS=e up catalys TBI=thrott super char control mo ESS=e (per 13 Cl	p=horsepower; kw=ki NG=compressed/liqu HDD=ligh/medium/hi emission control syste t; DPF=diesel particule body fuel injection; rger; CAC=charge aidulue; EM=engine mo engine shuldown syste CR 1956.8(a)(5(X)): EM 1956.8(a)(5(X)): EM=1956.8(a)(5(X)): EM=1956.8(a)(A)(a)(A)(A)(A)(A)(A)(A)(A)(A)(A)(A)(A)(A)(A)	iowatt; hi efied natu eavy heav em; TWC/ date filter; SFI/MFI= r cooler; l ddification em (per 1; Exempt=6	r=hour; jral gas; LPG=liquefi y-duty diesel; UB=u OC=three-way/oxidiz PTOX=periodic trap- sequential/multi port EGR / EGR-C=exhau; ; 2 (prefix)=parallel; 3 CCR 1956.8(a)(6)/ exempted per 13 CCF	ed petroleum gas; E85=85% etr rban bus; HDO=heavy duty Otto ing catalyst; NAC=NOx adsorpt oxidizer; HOZS/IO2S=heated/ox fuel injection; DGI=direct gasoli st gas recirculation / cooled EGF (2) (sufflx)=in series; NAM: 300=30 gtx NOx (ox 13	anol fuel; MF=mul; ; ; ; ; on catalyst; SCR- ;ygen sensor; HAF ne injection; GCAI ;; PAIR/AIR=pulse CCR 1956.8(a)(6)(G fuel systems; N/	if fuel a.k.a. BF J / SCR-N=sela S/AFS=heated RB=gaseous ca d/secondary air C); APS =interr A=not applicable	R 86.abc=Title 40, Code of Federal Regulation bi fuel; DF=dual fuel; FF=flexible fuel; civic catalytic reduction – urea / – ammonia; Nar-huel-ratio sensor (a.k.a., universal or linear fourefor. ID/DD1=indirect/direct diesel injection; SPL=smoke puff limiter; ECM/PCM al Combustion auxiliary power system; ALT=a e (e.g., Otto engines and vehicles);	WU (prefix) =warm- oxygen sensor); n; TC/SC=turbo/ t=engine/powertrain			

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on ponventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14				*	15.5	15.5	0.01	0.01	*	*
FEL	*	-7.	1.20	1.20	1.2	1.2	*	*	*	*	*	+
CERT	0.01	0.000	1.05	0.94	1.1	0.9	0.04	0.01	0.001 -	0.007	*	*
NTÉ	0.21		1.80		1.8		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Npl-to-Exceed; STO=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=npn-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=iormaldehyde; (Rev.: 2007-02-25)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [OTTO engines] and the incorporated 40CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Executed at El Monte, California on this _______ day of December 2008.

Annette Hebert, Chief

Rophael Sumowity

Mobile Source Operations Division