

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1580 New On-Road Heavy-Duty Engines Page 1 of 2 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAN	IILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
2000	2009 9GMXH06.659		- 5.0	D:	PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC,	EUD				
			6.6	Dieset	Diesel	LHDD	PTOX	EMD				
	'ENGINE'S IDLE											
EMISSIO	NS CONTROL	ADDITIONAL IDLE EMISSIONS CONTROL®										
	ESS	N/A										
ENGINE (L)			ENCINE MODE								
		ENGINE MODELS / CODES (rated power, in hp)										
0.0	6.6 LMM / 2 (300), LMM / 3 (300), LMM / 4 (330), LMM / 5 (330), LMM / 6 (250)											
L												
		gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 85.abc: w=kilowatt; hr=hour;										
T=not appli L=liter: hrs	cable; GVWR=gros: =horsepower; kw=ki	s vehicle v	veight rating; 13 CCI	₹xyz=Title 13, California Code o	f Regulations, Sect	on xyz; 40 CF	86.abc=Title 40. Code of Federal Regulations	Section B6 abov				
								, 000,001 00.000,				
2 (M/H H	IDD=light/medium/s	ciicu natu	rai gas; ∟ru=liquen	en petroleum gas; E85=85% eth	anol f uel; MF =mult	fuel a.k.a. BF:	=bi fuel; DF=dual fuel; FF=flexible fuel;					
3 =08-05	pipolog eneted a sete	avy neav	y-duty diesel; UB=ur	ban bus; HDO=heavy duty Otto;				/				
up catalyst:	DPF=diesel nerticul	m; IWC/(DC=three-way/oxidiz	ng calalyst; NAC=NOx adsorption	on catalyst; SCR-L	/ SCR-N=selec	tive catalytic reduction – urea / – ammonia; W	U (prefix) =warm-				
TBI=throttle	body fuel injection:	SFI/MFI=	sequential/multi-rort	fuel injection: DCI refront results	ygen sensor, MAF	AN-S=neated/a	ur-fuel-ratio sensor (a.k.a., universal or linear o	kygen sensor);				
super charg	јег, CAC=charge air	cooler; E	GR / EGR-C=exhaus	it gas recirculation / cooled EGR:	: PAIR/AIR=nulsed	p≕gaseous cart /secondan/ air i	puretor; IDI/DDI=indirect/direct diesel injection; njection; SPL=smoke puff limiter; ECM/PCM=	TC/SC=lurbo/				
							l combustion auxiliary power system; ALT=alti (e.g., Olto engines and vehicles);	ernative method				
EMD=e	ngine manufacturer	diagnostic	system (13 CCR 19)	(1); OBD=on-board diagnostic s	vstem (13 CCR 19)	1 1)	(e.g., e origines and Yelliucs),	ļ				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		РМ		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	* 7		*	*	15.5	15.5	0.01	0.01	*	*
FEI.	*	*	1.30	1.30	1.3	1.3	*	*	*	*	*	
CERT	0.04	0.00	1.13	1.07	1.14	1.07	0.4	0.10	0.000	0.000	*	-
NTE	0.21		1.95		2.0		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour: FTP=Federal Test Procedure: EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap: FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide: PM=particulate matter: HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.



GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1580 New On-Road Heavy-Duty Engines Page 2 of 2 Pages

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of April 2008.

Annette Hebert, Chief

Mobile Source Operations Division