California Exvironmental Protection Asence		EXECUTIVE ORDER A-021-0489			
	CUMMINS INC.	New On-Road Heavy-Duty Engines			
AIR RESOURCES BOARD		Page 1 of 1 Pages			

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE ¹	STANDARDS & TEST	INTENDED SERVICĘ	ECS & SPECIAL FEATURES	DIAGNOSTIC ⁶ EMD		
		OILLO (L)		PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC,			
2009	9CEXH0661MAB	10.8	Diesei	Diesel	UB	PTOX			
PRIMAR) EMISSIC	ARY ENGINE'S IDLE SSIONS CONTROL 5 SSIONS CONTROL 5								
E	EXEMPT N/A								
ENGINE (NE (L) ENGINE MODELS / CODES (rated power, in hp)								
10.8	ISM 330 / 2731;FR20134 (330), ISM 280 / 2731;FR20135 (291)								
*	· · · · · · · · · · · · · · · · · · ·								
•									

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; =itter; hp=horsepower; kw=kilowatt; hr=hour;

CNG/LNG=compressed/liquefied riatural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/W/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

Energy High result reaction and the series;
 ECS-emission control system;
 TWC/CC=hree-way/oxidizing catalyst;
 NAC=NOx adsorption catalyst;
 SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia;
 WU (prefix) =warm-up catalyst;
 DPF=desel particulate filter;
 PTOX=periodic trap oxidizer;
 HO25/025=heated/oxygen sensor;
 HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor);
 SUPF=dised particulate filter;
 PTOX=periodic trap oxidizer;
 HO25/025=heated/oxygen sensor;
 CARB=gaseous carburation;
 DIF/HFI=sequential/multi port fuel injection;
 DGF=direct dasseline injection;
 CARB=gaseous carburation;
 IDFIDIE through and the sensor;
 SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia;
 WU (prefix) =warm-up catalyst;
 DFF=desel particulate filter;
 PTOX=periodic trap oxidizer;
 DGF=direct dasseline injection;
 CARB=gaseous carburation;
 DIFIDIE transmission;
 DIFIDIE transmission;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(X)(1): 30g/ar NOx (per 13 CCR 1956.8(a)(5)(C); APS =Internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

İn	NMHC		NOx		NMHC+NOx		со		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	·FT₽	EURO	FTP	EURO	FTP (EURO
STD	0.5	0.5	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	•	2.5	2.5	*	•	*	*	*	+
CERT	0.01	0.01	*	•	2.2	1.7	0.00	0.00	0.002	0.001	*	*
NTE	0	.6		*	3	3.1	19	3.4	0.	02		*

g/bhp-tm=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing: NTE=Nol-to-Exced; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of February 2009.

Annette Hebert, Chief Mobile Source Operations Division