

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		IILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC		
				D'anal	PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC,	EMD		
2009	9CEXH0912XAQ 14.9		Diesel	Diesel	HHDD	SCR, PTOX				
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL  ADDITIONAL IDLE EMISSIONS CONTROL										
30g N/A										
ENGINE (	L)	ENGINE MODELS / CODES (rated power, in hp)								
14.9	14.9 See attachment for engine models and ratings									
L=liter; hp	* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; Leilter; hp=horsepower, kw=kilowatt, hr=hour;									
CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;  L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;										
ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MF=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor, IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge eir cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;										
ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);										

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.30	0.30	0.30	0.30	*	*	*	*	*	*
CERT	0.001	0.00	0.20	0.16	0.20	0.16	0.0	0.0	0.01	0.00	*	*
NTE	0.21		0.45		0.45		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-25)

**BE IT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

19 KL

Executed at El Monte, California on this \_\_\_

\_ day of November 2009.

Annette Hebert, Chief
Mobile Source Operations Division

## **Engine Model Summary Template**

61/21/11

# Hoshment: #-021-0514
page 1 of 1 111111

	17					A Comment	3		/
9.Emission Control svice Per SAE J1930	CRC, PTOX,	SCRC, PTOX,	sdrc, Ртф <sup>х</sup> ,	sciec, Prox,	scrc, Prox,	SCRO, PTOX,	sс <sub>Р</sub> С, ртох,	SØRC, PTOX,	SCRC, PYOX,
9.Em IeDevice	معد	S	SC	S	SC	SC	S	S	9
8.Fuel Rate: 9.Emission Control (Ibs/hr)@peak torqueDevice Per SAE J1930	143	143	126	143	143	126	143	126	110
7.Fuel Rate: mm/stroke@:peak torque	354	. 354	312	354	354	312	354	312	272
6.Torque @ RPM (SEA Gross)	1850@1200	1850@1200	1650@1200	1850@1200	1850@1200	1650@1200	1850@1200	1650@1200	1450@1200
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	166	166	166	162	162	162	166	166	155
4.Fuel Rate: 3.BHP@RPM mm/stroke @ peak HP (SAE Gross) (for dieset only)	248	248	248	242	242	242	248	248	232
3.BHP@RPM (SAE Gross)	452@1977	452@1977	452@1977	439@1977	439@1977	439@1977	452@1977	452@1977	411@1977
2.Engine Model	ISX15 500ST	ISX15 500	ISX15 500	ISX15 485ST	ISX15 485	ISX15 485	ISX15 500V	ISX15 500V	ISX15 455MC
1.Engine Code	3348;FR10818	3348;FR10817	3348;FR10816	3348;FR10815	3348;FR10814	3348;FR10813	3348;FR10825	3348;FR10822	3348;FR10848
Engine Family 1.Engine Code 2.Engine Model	9CEXH0912XAQ 3348;FR10818 ISX15 500ST	9CEXH0912XAQ 3348;FR10817	9CEXH0912XAQ 3348;FR10816	9CEXH0912XAQ 3348;FR10815 ISX15 485ST	9CEXH0912XAQ 3348;FR10814	9CEXH0912XAQ 3348;FR10813	9CEXH0912XAQ 3348;FR10825	9CEXH0912XAQ 3348;FR10822 ISX15 500V	9CEXH0912XAQ 3348;FR10848 ISX15 455MC

DOE, TC, CAC, ECM, ECA,
OC, SCA, PTOX