DETROIT DIESEL CORPORATION

EXECUTIVE ORDER A-290-0129-1 New On-Road Heavy-Duty Engines Page 1 of 2 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

0												
MODEL	ENCINE FAM	ENGINE FAMILY		FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
YEAR	ENGINE PAMIL		SIZES (L)		PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC, PTOX	EMD				
2009	9DDXH14.8	EED	14.8	Diesel	Diesel	HHDD	PIOX					
PRIMARY ENGINE'S IDLE			ADDITIONAL IDLE EMISSIONS CONTROL ⁵									
EMISSIC	EMISSIONS CONTROL 5		N/A.									
	30g											
ENGINE	ENCINE MODELS (CODES (rated power, in hp)											
14.8	(-)			See attachmen	it for engine m	odels and r	atings					
14.0												
*=not applicable; GVWR=gross vehicle weight rating: 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CPR 86.abc=Title 40, Code of Federal Regulations												
									=not app	licable; GVWR=gros =horsepower; kw=k	s vehicle	weight rating; 13 CC
1 CNG/I	NG=compressed/lim	refied nat	ural das: LPG=lique	fied petroleum gas; E85=85% eth	nanol fuel; MF= mu	ti fuel a.k.a. Bl	F=bi fuel; DF=dual fuel; FF=flexible fuel;					
2 L/M/H	HDD=light/medium/h	eavy hea	vy-duty diesel; UB≂ı	urban bus; HDO=heavy duty Otto		KAROD Namel	estive entallidic reduction – urea / – ammonia: V	WLI (prefix) =warm-				
3 ECS=6	emission control systi	em: TWC	:/OC=three-way/oxidi	zing catalyst; NAC=NOx adsorpt	ion catalyst; our	S/AFS=heated	ective catalytic reduction – urea / – ammonia; Mair-fuel-ratio sensor (a.k.a., universal or linear arburetor; IDI/DDI=IndIrect/direct diesel injection	oxygen sensor);				
up catalys	t: DPF=diesel partic	ulate filter • SFVMFI	; PTOX=periodic ira =sequential/multi poi	t fuel injection; DGI=direct gasoli	ne injection; GCA	RB=gaseous ca	arburetor; IDI/DDI=indirect/direct diesel injection r injection; SPL=smoke puff limiter; ECM/PCM	n; TC/SC=turbo/ l=engine/powertrain				
super cha	rger: CAC=charge a	ir caoler;	EGR / EGR-G-EXIA	usi gas recirculation i cooled Lor	c, i rancomo para							
control mo	odule; EM=engme m	odification	1; Z (prefix)-parane	, (z) (Bullix) and School	CCD 4056 9/aVCV	Ch. APS minter	nal combustion auxiliary power system; ALT=a	Iternative method				
control module; EM=engine modification; 2 (prefix)=parallet; (2) (surfix)=in series, ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/in NOx (per 13 CCR 1956.8(a)(6)(C); APS ≓internal combustion auxiliary power system; ALT=alternative ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); [per 13 CCR 1956.8(a)(6)(D); Exemptr≔exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);												

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

. 1	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
in g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
			- 1	*	*	*	15.5	15.5	0.01	0.01	*	*
STD	0.14	0.14	1.40	1 16	1.3	1.3	*	*	*	*	*	*
EL	*		1.16	1.10			0.3	0.03	0.000	0.001	*	*
CERT	0.02	0.01	1.08	1.05	1.09	1.06						*
NTE	0.21		1.	1.74		2.0		19.4		0.02		omicrions

g/bhp-hr=grans per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=tormaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending final approval of "Certified Clean Idle" vehicle label. The manufacturer has until November 1, 2008 to resolve concerns on this conditional certification. This Executive Order is effective through November 1, 2008; engines produced after this date are not covered by this Executive Order unless provided with a "Certified Clean Idle" label approved by ARB. In addition, the engine models listed above are certified on the condition that vehicles into which the conditionally certified engines are installed and to which were affixed a "Certified Clean Idle" label that does not have final ARB approval shall have an ARB approved "Certified Clean Idle" label affixed no later than December 31, 2009.

This Executive Order hereby supersedes Executive Order A-290-0129 dated May 23, 2008.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

__ day of July 200

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Template

A-290-0129-1

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak H (for diesel only)	5.Fuel Rate: P (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: os/hr)@peak torqu	9.Emission Control eDevice Per SAE J1930
the state of the s	CHARLES AND THE PARTY OF THE PA	District of the second						and the suit of the same of th	TON TO 010
THE RESERVE THE PROPERTY OF TH	The state of the second of the second	DD15	455@1800	265	158	1550@ 124 0	273	112	ECM, TC, CAC
9DDXH14.8EED		and the state of t			166	1550@1240	273	112	EGR, DOC,
9DDXH14.8EED		DD15	475@1800				293	120	DPF
9DDXH14.8EED	III	DD15	455@ 1800	265	158	1650@1240			(all ratings)
9DDXH14.8EED	IV	DD15	475@1800	278	166	165 0@ 124 0	293	120	(4111411195)
	V	DD15	505@1800	288	172	1650@1240	293	120	
9DDXH14.8EED			455@1800	265	158	1750@1240	311	127	
9DDXH14.8EED	VI	DD15			166	1750@1240	311	127	
9DDXH14.8EED	VII	DD15	475@1800				311	127	
9DDXH14.8EED	VIII	DD15	515@1800	296	177	1750@1240			
9DDXH14.8EED	IX	DD15	475@1800	27 5	164	1850@1240	327	134	
,		DD15	500@1800	290	173	1850@1240	327	134	
9DDXH14.8EED	X		530@1800		180	1850@1240	327	134	
9DDXH14.8EED	ΧI	DD15					327	134	
9DDXH14.8EED	XII	DD15	560@ 1800	320	191	1850@1240	321	101	
Querran									