## DETROIT DIESEL CORPORATION

EXECUTIVE ORDER A-290-0129 New On-Road Heavy-Duty Engines Page 1 of 2 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMI	LY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS	ECS & SPECIAL FEATURES 3 DDI, TC, CAC, ECM, EGR, OC,	DIAGNOSTIC 6				
2009	9DDXH14.8E	9DDXH14.8EED 14.8		Diesel	Diesel	HHDD	PTOX	EMD				
i .	Y ENGINE'S IDLE INS CONTROL	ADDITIONAL IDLE EMISSIONS CONTROL <sup>5</sup>										
30g		N/A.										
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)												
14.8		See attachment for engine models and ratings										
L=liter; hp CNG/LI L/M/H I ECS=e	:=horsepower; kw=kik NG=compressed/lique HDD=light/medium/hea mission control systen	owatt; hr- fied natur svy heavy n; TWC/0	=hour; ral gas; LPG=liquefi /-duty diesel; U8=u DC=three-way/oxidiz	ed petroleum gas; E85=85% eth rban bus; HDO=heavy duty Otto; ing catalyst; NAC=NOx adsorpti	anol fuel; MF=mult	i fuel a.k.a. B	FR 86.abc=Title 40, Code of Federal Regulations F=bi fuel; DF=dual fuel; FF=flexible fuel; ective catalytic reduction – urea / – ammonia; W	/U (prefix) =warm-				
TBI=throttle super char- control mod ESS=ed (per 13 CC	e body fuel injection; ger; CAC≃charge air dule; EM=engine mod ngine shutdown syster R 1956.8(a)(b); Ex	SFI/MFI=s cooler; E dification; m (per 13 kempt=ex	sequential/multi port GR / EGR-C=exhau 2 (prefix)=parallel; CCR 1956.8(a)(6)(/ tempted per 13 CCF	fuel injection; DGI=direct gasolir st gas recirculation / cooled EGR (2) (suffix)=in series; a)(1); 30g=30 g/hr NOx (per 13 C R 1956.8(a)(6)(B) or for CNG/LNG	ne injection; GCAR; PAIR/AIR=pulser CCR 1956.8(a)(6)(C i fuel systems; N/A	B≖gaseous ca i/secondary ai i); APS =inter ≔not applicabl	Wair-fuel-raffo sensor (a.k.a., universal or linear or arburetor; IDV/DDI=indirect/direct diesel injection; r injection; SPL=smoke puff limiter; EGM/PCM= pal combustion auxiliary power system; ALT=alt le (e.g., Otto engines and vehicles);	TC/SC=turbo/ engine/powertrain				
EMD=	engine manufacturer d	liagnostic	system (13 CCR 19	71); OBD=on-board diagnostic s	ystem (13 CCR 19	71,1};						

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	+
FEL	*	•	1.16	1.16	1.3	1.3	*	*		*	*	*
CERT	0.02	0.01	1.08	1.05	1.09	1.06	0.3	0.03	0.000	0.001	*	•
NTE	0.21		1.74		2.0		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

**BEIT FURTHER RESOLVED:** Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

**BE IT FURTHER RESOLVED:** Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.8.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

## **DETROIT DIESEL CORPORATION**

EXECUTIVE ORDER A-290-0129 New On-Road Heavy-Duty Engines Page 2 of 2 Pages

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

**BE IT FURTHER RESOLVED:** The listed engine models are conditionally certified pending final approval of "Certified Clean Idle" vehicle labels. The manufacturer has until June 30, 2008 to resolve concerns on this conditional certification. This Executive Order is effective through June 30, 2008; engines produced after this date are not covered by this Executive Order.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_ day of May 2008.

Annette Hebert, Chief

Mobile Source Operations Division

## **Engine Model Summary Template**

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5,Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Ra <b>te:</b> mm/stroke@pe <b>ak</b> torque	8.Fuel Rate: os/hr)@peak torque	9.Emission Control eDevice Per SAE J1930
Engine Family	(,Dingo					455051240	273	112	ECM, TC, CAC
9DDXH14.8EED		DD15	455@1800		158	1550@1240	273	112	EGR, DOC,
9DDXH14.8EED	11	DD15	475@1800	278	166	1550@12 <b>40</b> 1650@124 <b>0</b>	293	120	DPF
9DDXH14.8EED	lll.	DD15	455@ 1800		158	1650@1240	293	120	(all ratings)
9DDXH14.8EED	ΙV	DD15	475@1800		166	1650@1240	293	120	
9DDXH14.8EED	V	DD15	505@1800		158	1750@1240	311	127	
9DDXH14.8EED	VI	DD15	455@1800		166	1750@1240	311	127	
9DDXH14.8EED	VII	DD15	475@1800		177	1750@1240	311	127	
9DDXH14.8EED	VIII	DD15	515@1800		164	1850@1240	327	134	
9DDXH14.8EED	ΙΧ	DD15	475@1800 500@1800		173	1850@1240	327	134	
9DDXH14.8EED	X	DD15	530@1800		180	1850@1240	327	134	
9DDXH14.8EED	ΧI	DD15	560@1800		191	1850@1240	327	134	
9DDXH14.8EED	XII	DD15	960@1800	020	*				