Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAM	ENGINE FAMILY		FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6 EMD			
YEAR					PROCEDURE	CLASS	HPDI, ECM, TC, CAC, EGR, OC,				
2009	9WFSH0912XAL 14.9		14.9	BF (CNG / Diesel)	Diesel	HHDD	PTOX				
	Y ENGINE'S IDLE ONS CONTROL			ADD	ITIONAL IDLE EN	IISSIONS CO	NTROL <sup>5</sup>				
EXEMPT		N/A									
ENGINE (	E (L) ENGINE MODELS / CODES (rated power, in hp)										
14.9	ISXG 450ST / EDS-10011753 (450), ISXG 450 / EDS-10011755 (450)										
14.9 ISXG 400ST / EDS-10011883 (400), ISXG 400 / EDS-10011757 (400)					S-10011757 (400)						
*					*						
+		*									
L≃liter; hp CNG/L 2 L/M/H I	=horsepower; kw=k NG=compressed/liqu HDD=light/medium/h	ilowatt; hi lefied natu eavy heav	r=hour; ral gas; LPG=liquef y-duty dieset; UB=u	ied petroleum gas; E85=85% eth irban bus; HDO=heavy duty Otto	nanol fuel; MF=mul	tifuela.k.a. BF	R 86.abc=Title 40, Code of Federal Regulations =bi fuel; DF=dual fuel; FF=flexible fuel;				
up catalyst TBI=throttl super char control mo	t; DPF=diesel particu le body fuel injection; ger; CAC≂charge ai dule; EM=engine m	ulate filter; SFVMFI= ir cooler; I odification;	PTOX=periodic trap sequential/multi por EGR / EGR-C=exhau 2 (prefix)=parallel;	o oxidizer; HO2S/O2S=heated/ox fuel injection; DGI=direct gasoli ust gas recirculation / cooled EGR (2) (sufflx)=in series;	tygen sensor; HAF ne injection; GCAF R; PAIR/AIR=pulse	S/AFS=heated/ IB=gaseous car d/secondary air	ctive catalytic reduction – urea / – ammonia; W air-fuel-ratio sensor (a.k.a., universal or linear or buretor; IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM=	xygen sensor); ; TC/SC=turbo/ =engine/powertrain			
ESS≍e (per 13 CC	engine shutdown syst CR 1956.8(a)(6)(D);	em (per 10 Exempt=e	3 CCR 1956.8(a)(6)( exempted per 13 CC	A)(1); <b>30g</b> =30 g/hr NOx (per 13 ( R 1956.8(a)(6)(B) or for CNG/LN(	CCR 1956.8(a)(6)(0 3 fuel systems; <b>N/</b> A	i); APS =intem i=not applicable	al combustion auxiliary power system; ALT=all e (e.g., Otto engines and vehicles);	temative method			

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14			•	•	15.5	15,5	0.01	0.01	+	•
FEL	•	•	0.80	0.80	*	4	•	•	•		•	*
CERT	80.0	0.03	0.74	0.64		•	14.6	0.2	0:005	0,004	•	•
NTE	0.21		1.20		•		*		0.02		•	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

**BE IT FURTHER RESOLVED:** At the request of the manufacturer, certification to the FEL(s) listed above is subject to the following terms, limitations and conditions. (i) The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard and will be used for determining compliance of any engine in this family. (ii) Engines in this family will not participate in any averaging, banking, or trading (ABT) programs. And, (iii) The FEL(s) will not be revised to any levels above those indicated above.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2008.

Annette Hebert, Chief
Mobile Source Operations Division

Raphael Susnowith