CUMMINS INC.	New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

			ENGINE	FUEL TYPE	STANDARDS		ECS & SPECIAL FEATURES	DIAGNOSTIC				
YEAR	YEAR		SIZES (L)	· · · · · · · · · · · · · · · · · · ·	PROCEDURE	CLASS ²	DDI, TC, CAC, ECM, EGR, OC,	EMD				
2009	9CEXH0408	408BAG 6.7		Diesel	Diesei	MHDD	PTOX					
PRIMARY	ENGINE'S IDLE			ADD		AISSIONS CO	NTROL ⁵					
	30q		N/A									
ENGINE (E (L) ENGINE MODELS / CODES (rated power, in hp)											
6.7	7 See attachment for engine models and ratings											
*	*											
*				·····	*							
*					÷							
								0				

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.ab =liter; hp=horsepower; kw=kilowat; hr=hour;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; z L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

³ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NCe=N0× adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction -- urea / -- ammonia; WU (prefix) =warm-interactive catalyst; DPF=dissel particulate filler; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); Up catalyst; DPF=dissel particulate filler; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; CARB=gaseous carburetor; 1DI/DDI=indirect/direct dissel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke pulfi imiter; ECM/PCM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in senies; ESS=perior Biotecom sufficient pulsed (2) USE 1055 8//sU/2/1011 and 100 (prefix) 2005 1055 8//sU/2/1011 and 1055 8//sU/2/1011 an

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

NMHC		NOx		NMHC+NOx		co		PM		HCHO	
FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURÓ
0.14	0.14	*	*	٠	*	15.5	15.5	0.01	0.01	*	*
*	*	1.40	1.40	1.4	1.4	*	+	*	*	*	*
0.01	0.000	1.37	1.35	1.38	1.35	0.3	0.00	0.001	0.000	*	*
0.	21	2.	10	2	2.1	1	9.4	0	.02		*
	NM FTP 0.14 * 0.01 0.	NMHC FTP EURO 0.14 0.14 * * 0.01 0.000 0.21	NMHC N FTP EURO FTP 0.14 0.14 * * * 1.40 0.01 0.000 1.37 0.21 2.	NMHC NOx FTP EURO FTP EURO 0.14 0.14 * * * * 1.40 1.40 0.01 0.000 1.37 1.35 0.21 2.10 2.10	NMHC NOx NMHC FTP EURO FTP EURO FTP 0.14 0.14 * * * * * * 1.40 1.40 1.4 0.01 0.000 1.37 1.35 1.38 0.21 2.10 22 2.10 22	NMHC NOx NMHC+NOx FTP EURO FTP EURO FTP EURO 0.14 0.14 * * * * * * * 1.40 1.40 1.4 1.4 0.01 0.000 1.37 1.35 1.38 1.35 0.21 2.10 2.1 1.4 1.4	NMHC NOx NMHC+NOx C FTP EURO FTP EURO FTP EURO FTP 0.14 0.14 * * * * 15.5 * * 1.40 1.40 1.4 1.4 * 0.01 0.000 1.37 1.35 1.38 1.35 0.3 0.21 2.10 2.1 1 1 1	NMHC NOX NMHC+NOX CO FTP EURO FTP EURO FTP EURO 0.14 0.14 * * * 15.5 15.5 * * 1.40 1.40 1.4 1.4 * * 0.01 0.000 1.37 1.35 1.38 1.35 0.3 0.00 0.21 2.10 2.1 19.4	NMHC NOX NMHC+NOX CO F FTP EURO FTP EURO FTP EURO FTP EURO FTP O.14 0.14 * * * 15.5 15.5 0.01 * * 1.40 1.4 1.4 * * * * 0.01 0.000 1.37 1.35 1.38 1.35 0.3 0.00 0.001 0.21 2.10 2.1 19.4 0 0 0 0	NMHC NOX NMHC+NOX CO PM FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO 0.14 0.14 * * * 15.5 15.5 0.01 0.01 * * 1.40 1.4 1.4 * * * * 0.01 0.000 1.37 1.35 1.38 1.35 0.3 0.00 0.001 0.000 0.21 2.10 2.1 19.4 0.02	NMHC NOx NMHC+NOx CO PM H0 FTP EURO FTO EURO FTO EURO

International destination in the second seco (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOX] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

California Environmental Protection Agency	CUMMINS INC.	EXECUTIVE ORDER A-021-0511 New On-Road Heavy-Duty Engines
--	--------------	--

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of October 2009.

Annette Hebert, Chief Mobile Source Operations Division

CU#: 4-021-0511 Date: 09/23/09

Engine Model Summary Template

Attachurent 1. 21

ະຫຼາກe F amily	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control PDevice Per SAE J1930
ouExH0408BAG	3381;FR93118	ISB 300/PX6	300@2564	127	110	620@1600	123	66.2	RTOX, PCM
RCHXH0408BAG	3382;FR93125	ISB 280/PX6	280@2500	123	104	660@1600	12 9	69.7	PTOX, PCM,
DOFXH0408BAG	3381;FR93119	ISB 260/PX6	280@2500	123	104	660@1600	129	69.7	ртох, рсм,
actic XH0408BAG	3388;FR93126	ISB 240/PX6	260@2500	114	96.3	620@1600	121	65.4	ртох рсм,
))] ⇒ H0408BAG	3389;FR93120	ISB 280/PX6	260@2500	114	96.3	620@1600	121	65.4	ртох, есм,
CERH0408BAG	3388;FR93129	ISB 260/PX6	240@2500	108	90.9	620@1600	121	65.4	ртох, рсм,
NOEXH0408BAG	3389:FR93121	ISB 240/PX6	240@2500	108	90.9	620@1600	121	65.4	PTOX, POM,
MOEXH0408BAG	3388;FR93130	ISB 240/PX6	240@2500	108	90.9	560 <u>@</u> 1600	109	58.8	ртрх, рсм,
COLXE008BAG	3389;FR93122	ISB 240/PX6	240@2500	108	90.9	560@1600	109	58.8	PTOX, PCM
HOLXH0408BAG	3389;FR93123	ISB 220/PX6	220@2500	97	82.0	520@1600	103	55.5	PTOX, PCM,
SOEXH0408BAG	3389;FR93124	ISB 200/PX6	200@2400	97	78.5	520@1600	103	55.5	нтох, PCM,

EGR, PTOX EGY