

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMIL	Y ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6
''באר		312E3 (L)		PROCEDURE	CLASS 2	DDI, TC, CAC, ECM, EGR, OC,	EMD
2009	9CEXH0540LA	AQ 8.9	Diesel	Diesel	MHDD	PTOX, SCR	FIAID
	ENGINE'S IDLE		ADDI	TIONAL IDLE EN	IISSIONS CO	NTROL 5	
	30g			N	/A		
ENGINE (L)		ENGINE MODE	LS / CODES (ra	ted power, in	hp)	
8.9			See attachmen	t for engine m	odels and ra	atings	
*				•			
*				*			
*				•			
	cable; GVWR=gross v =horsepower; kw=kilov		CR xyz=Title 13, California Code o	f Regulations, Sect	ion xyz; 40 CF	R 86.abc=Title 40, Code of Federal Regulations	s, Section 86,abc;
19		•	fied petroleum gas; E85=85% eth		ifuela.k.a. BF	=bi fuel; DF=dual fuel; FF=flexible fuel;	

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto:

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NM	HC	N	Ox	NMH	C+NOx		;o	F	M	H	СНО
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	•	*
FEL.	+	*	0.38	0.38	0.38	0.38	*	*	*	*	+	•
CERT	0.00	0.00	0.22	0.23	0.22	0.23	0.0	0.0	0.00	0.00	*	+
NTE	0.	21	0.	57	0	57	19	9.4	0.	.02		•

g/bhp-hr=grams per brake horsepower-hour, FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rav.: 2007-02-26

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

ECS-emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter, PTOX=periodic trap oxidizer, HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBi=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler, EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS-conservative puriodic filter.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ___

___ day of December 2009.

Annette Hebert, Chief Mobile Source Operations Division

Engine Model Summary Template

				4.Fuel Rate:	5.Fuel Rate:		7.Fuel Rate:		
Engine Family	1.Engine Code	3.BHP@RPM mr 3.BHP@RPM mr Code 2.Engine Model (SAE Gross)	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (lbs/hr) @ peak HP 6.Torque @ RPM (for diesel only) (for diesels only) (SEA Gross)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	ak	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torqueDevice Per SAE J1930
9CEXH0540LAQ	9CEXH0540LAQ 3122;FR92592 ISL9 380	ISL9 380	365@2100	176	125	1300@1400	254	120	SCRC, PTOX,
9CEXH0540LAQ	9CEXH0540LAQ 3122;FR92594 ISL9 345	ISL9 345	330@2100	165	11.7	1150@1400	218	103	sorc, Prox,
9CEXH0540LAQ	3121;FR92589 ISL9 450	ISL9 450	420@2200	198	147	1250@1400	233	110	SCRG, PTOX,
9CEXH0540LAQ 3121;FR92591 ISL9 400	3121;FR92591	ISL9 400	380@2200	178	132	1250@1400	233	110	SCRC, RTOX,
							And the second second section is a second second second second section second s	AND THE RESIDENCE OF THE PROPERTY OF THE PROPE	The second of th

Charles of State of S