

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE ¹	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES ³	DIAGNOSTIC ⁶
2010	ACEXH0912XAP	14.9	Diesel	Diesel	HHDD	DDI, TC, CAC, ECM, EGR, OC, SCR-U, PTOX	EMD
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL ⁵		ADDITIONAL IDLE EMISSIONS CONTROL ⁵					
30g		N/A					
ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)						
14.9	See attachment for engine models and ratings						
¹ =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour; ² CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; ³ L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ⁴ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction - urea / - ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SF/MF=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ⁵ ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); ⁶ EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);							

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

In g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.35	0.35	*	*	*	*	*	*	*	*
CERT	0.001	0.000	0.25	0.19	*	*	1.4	0.0	0.002	0.000	*	*
NTE	0.21		0.52		*		19.4		0.02		*	

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.



This Executive Order hereby supersedes Executive Order A-021-0521 dated January 6, 2010.

Executed at El Monte, California on this 6 day of August 2010.

**Annette Hebert, Chief
Mobile Source Operations Division**

SUPERSEDED

Attachment page 1 of 1

Engine Model Summary Template

EO#: A-021-0521-1

07/30/2010

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
ACEXH0912XAP	3376;FR10812	ISX15 450ST	407@1977	231	154	1750@1200	333	135	SCRC, PTOX,
ACEXH0912XAP	3376;FR10811	ISX15 450ST	407@1977	231	154	1650@1200	312	126	SCRC, PTOX,
ACEXH0912XAP	3376;FR10809	ISX15 450	407@1977	231	154	1650@1200	312	126	SCRC, PTOX,
ACEXH0912XAP	3376;FR10808	ISX15 450	407@1977	231	154	1550@1200	291	118	SCRC, PTOX,
ACEXH0912XAP	3376;FR10805	ISX15 425ST	384@1977	221	154	1750@1200	333	135	SCRC, PTOX,
ACEXH0912XAP	3376;FR10804	ISX15 425ST	384@1977	221	154	1650@1200	312	126	SCRC, PTOX,
ACEXH0912XAP	3376;FR10803	ISX15 425	384@1977	221	154	1650@1200	312	126	SCRC, PTOX,
ACEXH0912XAP	3376;FR10802	ISX15 400ST	362@1977	212	141	1750@1200	333	135	SCRC, PTOX,
ACEXH0912XAP	3376;FR10801	ISX15 400ST	362@1977	212	141	1650@1200	312	126	SCRC, PTOX,
ACEXH0912XAP	3376;FR10800	ISX15 400	362@1977	212	141	1450@1200	272	110	SCRC, PTOX,
ACEXH0912XAP	3376;FR10824	ISX15 435V	404@1977	229	153	1450@1200	272	110	SCRC, PTOX,
ACEXH0912XAP	3490;FR10872	ISX15 450ST	407@1977	231	154	1750@1200	329	133	SCRC, PTOX,
ACEXH0912XAP	3490;FR10871	ISX15 450ST	407@1977	231	154	1650@1200	309	125	SCRC, PTOX,
ACEXH0912XAP	3490;FR10870	ISX15 450	407@1977	231	154	1650@1200	309	125	SCRC, PTOX,
ACEXH0912XAP	3490;FR10869	ISX15 450	407@1977	231	154	1550@1200	289	117	SCRC, PTOX,
ACEXH0912XAP	3490;FR10868	ISX15 425ST	384@1977	221	154	1750@1200	329	133	SCRC, PTOX,
ACEXH0912XAP	3490;FR10867	ISX15 425ST	384@1977	221	154	1650@1200	309	125	SCRC, PTOX,
ACEXH0912XAP	3490;FR10866	ISX15 425	384@1977	221	154	1650@1200	309	125	SCRC, PTOX,
ACEXH0912XAP	3490;FR10865	ISX15 400ST	362@1977	212	141	1750@1200	329	133	SCRC, PTOX,
ACEXH0912XAP	3490;FR10864	ISX15 400ST	362@1977	212	141	1650@1200	309	125	SCRC, PTOX,
ACEXH0912XAP	3490;FR10863	ISX15 400	362@1977	212	141	1450@1200	272	110	SCRC, PTOX,
ACEXH0912XAP	3490;FR10873	ISX15 435V	404@1977	229	153	1450@1200	272	110	SCRC, PTOX,

SCR-U, PTOX, DOC, ECM,
CAC, TC, DDI, EGR