**AIR RESOURCES BOARD** 

**California Environmental Protection Agency** 

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAN	IILY	ENGINE SIZES (L)	FUEL TYPE	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS	ECS & SPECIAL FEATURES <sup>3</sup> DDI. TC. CAC. ECM. EGR. OC.		
2010	AVPTH10.8	S01 10.8 Diesel Diesel HHDD DPF, SCR, SPL EMD							
PRIMARY EMISSIO	ENGINE'S IDLE			ADDI	TIONAL IDLE EN	IISSIONS COI	NTROL <sup>5</sup>		
	30g				N	/A			
ENGINE (	L)			ENGINE MODE	LS/CODES (rat	ted pow <mark>er, In</mark>	hp)		
10.8		See a	ttachment for er	ngine models and ratings	(clean idle eng	gin <b>es</b> are la	beled as 50-State compliant engines	5)	
* =not appli L=liter; hp= CNG/LM	cable; GVWR=gros =horsepower; kw=k IG=compressed/liqu	s vehicle v ilowatt; h lefied natu	weight rating; 13 CC r=hour; ıral gas; LPG=liquefi	R xyz=Title 13, California Code o ied petroleum gas; E85=85% eth	f Regul <b>at</b> ions, Sect anol fuel; MF=mult	ion xyz; <b>40 CF</b> I i f <b>uel</b> a.k.a. <b>BF</b>	R 86.abc=Title 40, Code of Federal Regulations =bi fuel, DF=dual fuel; FF=flexible fuel;	Section 86.abc;	

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Qtto;

Environmedication equipartities and the second equipart is a second equipart of the second equipart in the second equipart is a second equipart in the second equipart is a second equipart is a second equipart in the second equipart is a second equipart is a second equipart is a second equipart is a second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the second equipart in the second equipart is a second equipart in the seco

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=atternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NN	IHC	N	Ox	NMH	C+NOx	(	:0	P	M	н	сно
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	*	*	*	*
FEL			*	*	*	*	*	*	0.00	0.00	*	*
CERT	0.02	0.01	0.13	0.09	*	*	*	*	0.001	0.002	*	*
NTE	0.	21	0.	.30		*	1	9.4	0.	00		*

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ramp mode cycle supplemental emissions testing: NTE=Not4o-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of November 2009.

Annette Hebert, Chief **Mobile Source Operations Division** 

VUINO COMENTERIA CORDICATION

A 17 ACHWENT

A-242-0056

/ EM,EC,TC,CAC,DI,EGF	113.8	284.1	1493.6 @ 1200	149.6	248.9	405 @ 1800	D11H-405	N/A	/PTH10.1S01
EM, EC, TC, CAC, DI, EGF	113.9	284.3	1508.0 @ 1200	136.7	240.8	385 @ 1700	D11H-385	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	95.8	260.9	1379.4 @ 1100	128.2	225.9	365 @ 1700	D11H-365	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	82.5	235.2	1228.5 @ 1050	125.6	221.3	355 @ 1700	D11H-355	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	82.3	234.7	1235.6 @ 1050	114.3	201.4	325 @ 1700	D11H-325	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	114.7	286.2	1512.6 @1200	152.2	239.8	405 @ 1900	MP7-405M	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	103.1	257.3	1360.5 @ 1200	134.3	211.7	365 @ 1900	MP7-365M	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	91.6	228.5	1215.3 @1200	118.1	186.1	325 @ 1900	MP7-325M	N/A	/PTH10.1S01
EM,EC,TC,CAC,DI,EGF	121.8	304.0	1596.6 @ 1200	137.6	274.7	395 @ 1500	MP7-395C	N/A	/PTH10.8S01
EM,EC,TC,CAC,DI,EGF	112.5	280.8	1491.0 @ 1200	125.7	259.7	365 @ 1450	MP7-365C	N/A	/PTH10.8S01
EM, EC, TC, CAC, DI, EGF	104.9	261.7	1391.9 @ 1200	118.3	236.2	345 @ 1 <b>5</b> 00	MP7-345C	N/A	/PTH10.8S01
EM,EC,TC,CAC,DI,EGF	113.2	282.5	1492.6 @ 1200	148.8	247.6	405 @ 1800	MP7-405E	N/A	/PTH10.8S01
EM,EC,TC,CAC,DI,EGF	105.3	262.9	1393.2 @ 1200	127.6	212.4	3 <b>55 @</b> 1800	MP7-355E	N/A	/PTH10.8S01
SCEM, EC, TC, CAC, DI, EGF	96.7 Str	241.3	1282.0 @ 1200	116.2	188.1	325 @ 1850	MP7-325E	N / A	/PTH10.8S01
9.Emission Control Device Per SAE J1930	8.Fuel Rate: (bs/hr)@peak torg <b>ue</b> l	7.Fuel Rate: mm/stroke@peak torque (	6.Torque @ RPM (SEA Gross)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	3.BHP@RPM (SAE Gross)	2.Engine Model	1.Engine Code	ingine Family