FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1576-2 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6		
					PROCEDURE	CLASS 2	SFI, HO2S, TWC, 2HAFS			
2011	BFMXE06.8	BW5	6.8	Gasoline	Otto	HDO	01 1, 11020, 1110, 211/11 0	LIVID		
	ENGINE'S IDLE NS CONTROL	ADDITIONAL IDLE EMISSIONS CONTROL 5								
	N/A	N/A								
ENGINE (L	ENGINE MODELS / CODES (rated power, in hp)									
6.8	Motor Ho	F-450/550 Chassis Cab: BFA18N0505, BFA18N0506, BFA18N0507, BFA18N0508, BFA18N0509, BFA18N0510, BFA18N0511, BFA18N0520, BFA18N0521, BFA18N0522, BFA18Y0505, BFA18Y0506, BFA18Y0507; Step Van: BFA18R0505, BFA18R0506, BFA18R0507, BFA18R0510, BFA18R0520, BFA18R0530; Motor Home: BFA18Q0505, BFA18Q0506, BFA18Q0507, BFA18Q0508, BFA18Q0510, BFA18Q0520, BFA18Q0530, BFA18Q0531 (362 for all codes)								
*					*					
L=liter, hp= CNG/LN L/M/H H	-horsepower; kw= IG=compressed/lid IDD=light/medium/	kilowatt; h uefied natu neavy heav	r=hour; ural gas; LPG=liquef vy-duty diesel; UB=u	ied petroleum gas; E85=85% ethi rban bus; HDO=heavy duty Otto;	anol fuel; MF=mult	ifuel a.k.a. BF	R 86.abc=Title 40, Code of Federal Regulation =bi fuel; DF=dual fuel; FF=flexible fuel;			

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filier; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct dises linjection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; SPL=smoke puff limiter; ECM/PCM=engine/powertrain (profix) = 1.0 (PR) 1958 (la)(SV/AVI); ADS 31 (la)(SV/AVII); ADS 31 (la)(SV/AVIII); ADS 31 (la)(SV/AVIII); ADS 31 (la)(SV/AVIII); ADS 31 (la)(

ESS-engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		СО		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14		0.20	*	*	*	14.4	*	0.01	*	0.01	*
FEL	*	*		*	*	•	*	*	*	*	•	*
CERT	0.07	*	0.12	*	*	*	14.4	*	•	*	0.000	•
NTE	*		*		*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-25)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty) and 13 CCR 1971 (engine manufacturer diagnostic)

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1576-1 dated June 27, 2011.

Executed at El Monte, California on this

day of December 2011.

Annette Hebert, Chief
Mobile Source Operations Division