

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | ENGINE FAMI | LY | ENGINE SIZES (L) | FUEL TYPE 1 Flexible Fuel: | STANDARDS & TEST PROCEDURE | SERVICE CLASS | ECS & SPECIAL FEATURES 3 DIAGNO | | | |
|--------------------------------------------|---------------------------------------------------------------------|----------------------------------------------------------|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--|--|
| 2011 | BFMXE05.4BWC 5. | | 5.4 | Ethanol (E85) / Gasoline (Tier 2 Unleaded) | Otto | HDO | TWC, 2HO2S, SFI, 2HAFS | EMD | | |
| | Y ENGINE'S IDLE ONS CONTROL | | | | | | | | | |
| | N/A | /A N/A | | | | | | | | |
| ENGINE (| (L) | ENGINE MODELS / CODES (rated power, in hp) | | | | | | | | |
| 5.4 | | E450 Incomplete / BE414Y05, BE414W05 (255 for all codes) | | | | | | | | |
| * | | | | | * | | | | | |
| L=liter; hp 1 CNG/LI 2 L/M/H I | =horsepower; kw=k NG=compressed/liqu HDD=light/medium/h | ilowatt; iefied na eavy he | hr=hour; atural gas; LPG= eavy-duty diesel; | liquefied petroleum gas; E85=85% eth UB=urban bus; HDO=heavy duty Otto; | anol fuel; MF=mult | ifuela.k.a. BF | =bi fuel; DF=dual fuel; FF=flexible fuel; | | | |
| up catalyst; TBI=throttic super char | ; DPF=diesel particue body fuel injection; ger; CAC=charge ai | late filte SFI/MI r cooler | er; PTOX=periodi Fl=sequential/mul ; EGR / EGR-C= | ic trap oxidizer; HO2S/O2S=heated/ox ti port fuel injection; DGI=direct gasolir | ygen sensor; HAFS ne injection; GCAR | S/AFS=heated/a B=gaseous car | tive catalytic reduction – urea / – ammonia; air-fuel-ratio sensor (a.k.a., universal or linear buretor; IDI/DDI=indirect/direct diesel injectio injection; SPL=smoke puff limiter; ECM/PCN | oxygen sensor); n; TC/SC=turbo/ | | |
| (per 13 CC | R 1956.8(a)(6)(D); 1 | Exempt | exempted per 13 | a)(6)(A)(1); 30g=30 g/hr NOx (per 13 0 3 CCR 1956.8(a)(6)(B) or for CNG/LNG CR 1971); OBD=on-board diagnostic s | fue systems; N/A | =not applicable | al combustion auxiliary power system; ALT=a (e.g., Otto engines and vehicles); | alternative method | | |

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

| in | NMHC | | NOx | | NMHC+NOx | | со | | PM | | нсно | |
|----------|----------------|------|----------------|------|----------|------|----------------|------|----------------|------|------------------|------|
| g/bhp-hr | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO |
| STD | 0.14 [0.14] | * | 0.20 [0.20] | * | * | * | 14.4 [14.4] | * | 0.01 [0.01] | | 0.01 [0.01] | * |
| FEL | * | * | * | * | * | * | * | * | * | * | * | * |
| CERT | 0.07 [0.08] | * | 0.07 [0.14] | * | * | . * | 2.7 [4.4] | * | * | * | 0.003 [0.001] | * |
| NTE | * | | * | | * | | * | | * | | * | |

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

__ day of July 2010.

annualls FOR ANNETTE HERERT

Annette Hebert, Chief

Mobile Source Operations Division