1	California Environmental Protection Agency	NAVISTAR, Inc.	
	AIR RESOURCES BOARD		

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAM	LY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST		ECS & SPECIAL FEATURES	DIAGNOSTIC 6			
TEAN.			01220 (2)		PROCEDURE	CLASS ~	DDI, TC(2), CAC, ECM, EGR,	EMD			
2011	BNVXH04660GC 7.6		7.6	Diesel	Diesel	MHDD	OC(2), PTOX	CIVID			
PRIMARY	PRIMARY ENGINE'S IDLE										
EMISSIO	NS CONTROL		ADDITIONAL IDLE EMISSIONS CONTROL								
	ESS		N/A.								
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)											
7.6	A230H / 1151 (230); A230 / 1141 (230); A215 / 1121 (2 15)										
*	*										
CNG/L	* <										

L/M/H HDD=light/medium/heavy heavy-duty disel; UB=urban bus; HDO=heavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=dises | particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HATS/AFS=heated/air/uel-ratio sensor (a. k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFUMFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct disel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallei; (2) (suffix)=in series; ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS=intemal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(a)(6) or for CNG/LNG fuel system; N/A=not applicable (e.g., Oto engines and vehicles); EM=ensions method interview infancestin system (73 CCR 1956.8(a)(6)(6) or for CNG/LNG fuel system; S/A=not applicable (e.g., Oto engines and vehicles); EM=ensions distributed (fancestin system) (73 CCR 1956.8(a)(6)(6) or for CNG/LNG fuel system; S/A=not applicable (e.g., Oto engines and vehicles); EM=ensions distributed (fancestin system) (73 CCR 1956.8(a)(6)(6) or for CNG/LNG fuel system; S/A=not applicable (e.g., Oto engines and vehicles); EM=ensions distributed (fancestin system) (73 CCR 1956.8(a)(6)(6) or for CNG/LNG fuel system; S/A=not applicable (e.g., Oto engines and vehicles); EM=ension distributed (fancestin system) (fancestin system

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in NMHC		NOx		NMHC+NOx		co		PM		нсно		
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14			*	*	15.5	15.5	0.01	0.01	*	• *
FEL	*	*	0.50	0.50	*	*	*	*	*	*	*	*
CERT	0.08	0.02	0.30	0.32	*	*	4.8	0.1	0.001	0.000	* .	*
NTE	0.1	21	C).75		*	19).4	0.	02		

 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitroge (Rev.: 2007-02-)
 (Rev.: 2007-02-) (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of January 2011.

Annette Hebert. Chief Mobile Source Operations Division