Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAM	IILY ENGIN		STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
			· ·	PROCEDURE CLASS 2 Otto HDO 2TWC, SFI, 2HO2S(2)		N/A					
2011	BBYTE06.0	633 6.0	LPG	Otto	HDO						
1	' ENGINE'S IDLE NS CONTROL		AD	DITIONAL IDLE E	MISSIONS CO	NTROL 5					
	N/A	N/A									
ENGINE (L)		ENGINE MOI	DELS / CODES (ra	ited power, in	hp)					
6.0				GM6.0L / 1 (29	90)						
					_						
L=liter; hp 1 CNG/Li 2 L/M/H i 3 ECS=a up catalyst TBI=throttle super char- control mod 5 ESS=ei (per 13 CC	=horsepower; kw=ki NG=compressed/liqu HDD=light/medium/he mission control syste ; DPF=diesel particu e body fuel injection; ger; CAC=charge air Jule; EM=engine mo ngine shutdown syste R 1956.8(a)(6)(D); E	ilowatt; hr=hour; leffed natural gas; LPG eavy heavy-duty diesel; m; TWC/OC=three-wa: late filter; PTOX=perio SFI/MFI=sequential/m; r cooler; EGR / EGR-C dification; 2 (prefix)=perm (per 13 CCR 1956.8 Exempt=exempted per	leliquefied petroleum gas; E85=85% e UB=urban bus; HDO=heavy duty Ot y/oxidizing catalyst; NAC=NOx adson dic trap oxidizer; HO2S/O2S=heated/ ulti port fuel injection; DGI=direct gasc =exhaust gas recirculation / cooled Ec arallel; (2) (suffix)=in senies; (a)(6)(A)(1); 30g=30 g/hr NOx (per 13 13 CCR 1956.8(a)(6)(B) or for CNG/LI	othanol fuel; MF=multo; to; ption catalyst; SCR-loxygen sensor, HAF bline injection; GCAF R; PAIR/AIR=pulse 3 CCR 1956.8(a)(6)(0 NG fuel systems; N/A	ti fuel a.k.a. BF U / SCR-N=sele S/AFS=heated/ RB=gaseous car d/secondary air C); APS =intern A=not applicable	R 86.abc=Title 40, Code of Federal Regulation =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; V air-fuel-ratio sensor (a.k.a., universal or linear riburetor; IDVDDI=indirect/direct dissel injectior injection; SPL=smoke puff limiter; ECM/PCM all combustion auxiliary power system; ALT=a to (e.g., Otto engines and vehicles);	NU (prefix) ⇒warm- oxygen sensor); n; TC/SC=turbo/ l=engine/powertrain				
up catalyst TBI=throttle super charg control mod ESS=ed (per 13 CC	DPF=diesel particue body fuel injection; ger, CAC=charge air dule; EM≐engine mo ngine shutdown syste R 1956.8(a)(6)(D); E	ulate filter, PTOX=period SFI/MFI=sequential/m r cooler; EGR / EGR-Ci odification; 2 (prefix)=p em (per 13 CCR 1956.8 exempt=exempted per	dic trap oxidizer, HO2S/O2S=heated/ ulti port fuel injection; DGI=direct gasc =exhaust gas recirculation / cooled EC arallel; (2) (suffix)=in series; 8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13	oxygen sensor, HAF oline injection; GCAF GR; PAIR/AIR=pulse B CCR 1956.8(a)(6)(0 NG fuel systems; N/A	S/AFS=heated/ RB=gaseous car d/secondary air C); APS =intern A=not applicable	air-fuel-ratio sensor (a.k.a., universal or linear or rburetor, IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM al combustion auxiliary power system; ALT=a	oxygen s n; TC/SC I=engine/				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		co		PM		нсно		
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	
STD	0.14	*	0.20	*	*	*	14.4	*	0.01	*	0.01	*	
FEL	*	*	*	*	*	*	*	*	*	*	*	*	
CERT	0.07	*	0.14	*	*	*	6.5	*	0.003	*	0.001	*	
NTE	*					*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of January 2011.

Annette Hebert, Chief

Mobile Source Operations Division