Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6			
- ILAN		312E3 (E)		PROCEDURE	CLASS	TURBULE FOL	T			
2011	BCSTH0.51CN	0.51 KG/S	Compressed Natural Gas			TURBINE, ECM	N/A			
PRIMARY ENGINE'S IDLE EMISSIONS CONTROL		ADDITIONAL IDLE EMISSIONS CONTROL 5								
EXEMPT		N/A								
ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)								
0.51 KG/S		See attachment for engine models and ratings								
*		*								

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; =liter; hp=horsepower; kw=kilowatt; hr=hour;

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diésel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		СО		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	
FEL	*		*		*	•	*	*	*	*	*	*
CERT	0.06	0.05	0.05	0.06	*	*	0.6	0.5	0.001	0.001	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour, FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO-carbon magnetic. PM=narticulate matter: HCHO=formaldehyde: (Rev.: 2007-02-26) CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte. California on this day of August 2011.

> nnette Hebert, Chief Mobile Source Operations Division

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS-emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallet; (2) (suffix)=in series;

ESS-engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

Attachment 1 af 1

Engine Model Summary Template

A-338-0010 8/8/2011

Engine Family	1.Engine Code	2.Engine Model		4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak tord	9.Emission Control pueDevice Per SAE J19	
BCSTH0.51CNG	520193-300	65X-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	Turbonie NONE E	ECM
BCSTH0.51CNG	520193-600	65Y-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	MANAGEMENT AND DESCRIPTION OF THE PARTY OF T
BCSTH0.51CNG	529749-200	65W-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	**********************
BCSTH0.51CNG	529749-100	65Z-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	
BCSTH0.51CNG	520193-400	65X-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	Frank delikarin optimi an
BCSTH0.51CNG	520193-500	65Y-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	THE PERSON IN COLUMN TWO IS NOT THE PERSON IN
BCSTH0.51CNG	529749-400	65W-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	NONE	
BCSTH0.51CNG	529749-300	65Z-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	Ψ NONE	V