California Environmental Protection Agency	EXECUTIVE ORDER A-021-0563 New On-Road Heavy-Duty Engines
AIR RESOURCES BOARD	Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAM	ENGINE FAMILY		FUEL TYPE	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES	DIAGNOSTIC ⁶ N/A				
YEAR			SIZES (L)	010410	PROCEDURE	CLASS	TBI, TC, CAC, ECM, EGR, TWC,					
2012	CCEXH0540	CEXH0540LBH 8.9		CNG/LNG	Diesel	HHDD	HO2S					
PRIMARY ENGINE'S IDLE ADDITIONAL IDLE EMISSIONS CONTROL 5												
E	XEMPT			N/A								
ENGINE ([L)	ENGINE MODELS / CODES (rated power, in hp)										
8.9		ISL G 280 / 3519;FR93282 (280), ISL G 260 / 3519;FR93284 (260), ISL G 250 / 3519;FR93287 (250) ISL G 320 / 3519;FR93276 (320), ISL G 300 / 3519;FR93279 (300)										
L=liter; hp CNG/L	=horsepower; kw=k NG=compressed/liqu	ilowatt; hi efied natu	=hour; ral gas; LPG=liquef	ed petroleum gas; E85=85% eth	anol fuel; MF=mult		R 86.abc=Title 40, Code of Federal Regulations =bi fuel; DF=dual fuel; FF=flexible fuel;	s, Section 86.abc;				
³ ECS=er up catalyst TBI=throttle	mission control syste ; DPF=diesel particular e body fuel injection;	m; TWC/ late filter, SFI/MFI=	OC=three-way/oxidiz PTOX=periodic trap sequential/multi port	oxidizer; HO2S/O2S=heated/ox fuel injection; DGI=direct gasolin	on catalyst; SCR-U ygen sensor; HAFS he injection; GCAR	S/AFS=heated/ B=gaseous ca	ctive catalytic reduction – urea / – ammonia; W 'air-fuel-ratio sensor (a.k.a., universal or linear o rburetor, ID//DDI=indirect/direct diesei injection; injection; SPL=smoke puff limiter; ECM/PCM=	xygen sensor); TC/SC=turbo/				

super charger, CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertra control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EXS=proversion environment (2) COL 1021): (2) COL 1021): (2) COL 1021 (2) COL 1021 (2) COL 1021): (2) COL 1021 (2) COL 1021 (2) COL 1021): (2) COL 1021 (2) COL 1021): (2) COL 1021 (2) COL 1021 (2) COL 1021): (2) COL 1021 (2) COL 1021 (2) COL 1021): (2) COL 1021 (2) CO

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		CO		РМ		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	•	15.5	15.5	0.01	0.01	•	+
FEL	*	+			•	•	*	+	*	*	*	•
CERT	0.08	0.08	0.13	0.01	•	•	14.2	11.6	0.002	0.001	*	•
NTE	0.21		0.30		•		19.4		0.02		•	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of October 2011.

Annette Hebert, Chief Mobile Source Operations Division