California Environmental Protection Agency DETROIT DEISEL CORPORATION	EXECUTIVE ORDER A-290-0142 New On-Road Heavy-Duty Engines
---	--

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

	ENGINE FAMILY		FUEL TYPE	STANDARDS & TEST	INTENDED SERVICE CLASS	ECS & SPECIAL FEATURES				
1 Ersty		0,220 (2,		PROCEDURE		DDI, TC, CAC, ECM, EGR, OC,				
2012	CDDXH15.6GED	15.6	Diesel	HHDD	PTOX, SCR-U, AMOX	ENID				
PRIMARY	PRIMARY ENGINE'S IDLE 5									
EMISSIO	SIONS CONTROL ADDITIONAL IDLE EMISSIONS CONTROL									
	30g N/A									
ENGINE (INE (L) ENGINE MODELS / CODES (rated power, in hp)									
15.6	6 See attachment for engine models and ratings									
* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc;										

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=ftexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

³ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NC=NOX adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=disel particulate filter, PTOX=periodic trap oxidizer, HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.K.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor, IDI/DDI=indirect/direct/direct diesel injection; TC/SC=turbo/ super charger, CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine studyme surface (crefix) = parallel; (2) [suffix)=in series; AMOX: ammonia oxidation catalyst.

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1): 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempte-exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F)/(P)/(\$)=full/ partial with fine/ on-board diagnostic.

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOX		NMHC+NOx		CO		PM		нсно	
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20		*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	*		*	*	*	*	.*	*	*
CERT	0.000	0.000	0.13	0.09	+	*	0.1	0.01	0.003	0.000	*	*
NTE	0.	21	D	.30		*	19	9.4	0.	02		*

FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions g/bhp-hr=grams per brake horsepower-hour; testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitroge CD=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-(Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic system), and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order. ll

Ω

Executed at El Monte, California on this

day of December 2011.

FOR AGH

Annette Hebert, Chief Mobile Source Operations Division

ATTACHMENT 1 OF 1

Engine Model Summary Template A-290-0142

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control eDevice Per SAE J1930
CDDXH15.6GED	1	DD16	475@1800	270	160.3	1750@1240	308	125.8	ECM, TC, CAC
CDDXH15.6GED	11	DD16	500@1800	285	169.2	1750@1240	308	125.8	EGR, DOC,
CDDXH15.6GED	111	DD16	535@1800	307	181.7	1750@1240	308	125.8	DPF, SCR-12
CDDXH15.6GED	IV	DD16	500@1800	285	169.2	1850@1240	327	133.3	(all ratings)
CDDXH15.6GED	V	DD16	550@1800	316	187.0	1850@1240	327	133.3	DDI, AMOX
CDDXH15.6GED	VI	DD16	600@1800	346	204.8	1850@1240	327	133.3	
CDDXH15.6GED	VII .	DD16	475@1800	270	160.3	1950@1240	345.	141.0	V
CDDXH15.6GED	VIII	DD16	500@1800	285	169.2	2050@1240	364	148.7	for all ratings
CDDXH15.6GED	IX	DD16	550@1800	316	187.0	2050@1240	364	148.7	· · · · · · · · · · · · · · · · · · ·
CDDXH15.6GED	X	DD16	600@1800	346	204.8	2050@1240	364	148.7	