Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6 OBD(\$)			
YEAR			SIZES (L)	6:201	PROCEDURE	CLASS	DDI, TC(2), CAC, ECM, EGR,				
2013			3.0	Diesel	Diesel	LHDD	OC, PTOX, SCR-U, AMOX				
	NS CONTROL		INDIANO MININ	a tag uddal a Ac	DITIONAL IDLE EN	MISSIONS COM	NTROL 5	a ,aoireano S no secono			
30g		N/A									
ENGINE (ENGINE MODELS / CODES (rated power, in hp)										
3.0		F1C / 4P10 (161)									
L=liter; hp 1 CNG/LI 2 L/M/H I 3 ECS=ei up catalyst; TBI=throttle super charge	=horsepower; kw=k NG=compressed/liqu HDD=light/medium/h mission control syste ; DPF=diesel partict e body fuel injection; ger; CAC=charge ai	ilowatt; hi efied natu eavy heav m; TWC/ ilate filter; SFI/MFI= r cooler; I	r=hour; ural gas; LPG=liquefic y-duty diesel; UB=url OC=three-way/oxidizi PTOX=periodic trap sequential/multi port t EGR / EGR-C=exhaus	ad petroleum gas; E85=85% ban bus; HDO=heavy duty C ng catalyst; NAC=NOx adso soxidizer; HO2S/O2S=heated fuel injection; DGI=direct gas	ethanol fuel; MF=mul bito; rption catalyst; SCR-toxygen sensor; HAF oline injection; GCAF GR; PAIR/AIR=pulse	ti fuel a.k.a. BF J / SCR-N=seled S/AFS=heated/a RB=gaseous car d/secondary air	R 86.abc=Title 40, Code of Federal Regulation =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; V air-fuel-ratio sensor (a.k.a., universal or linear buretor; IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM	NU (prefix) =warm- oxygen sensor); n; TC/SC=turbo/			
5 ESS=er	ngine shutdown syst	em (per 13	3 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 1	3 CCR 1956.8(a)(6)(0); APS =interna	al combustion auxiliary power system; ALT=a	Iternative method			

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F)/(P)/(\$)=full/ partial/ partial with fine/ on-board diagnostic.

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	*	*	*	*	*	*	*	*	*	*
CERT	0.00	0.00	0.14	0.09	*	*	0.0	0.0	0.002	0.001	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

4 g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental Emission Test Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted December 12, 2002, as last amended March 22, 2012, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have three deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$25 per engine for the third deficiency in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2013 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-396-0006 dated March 12, 2013.

Executed at El Monte, California on this

day of January 2014.

Erik White, Chief

Mobile Source Operations Division