⊘ Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | ENGINE FAMILY | | ENGINE SIZES (L) | FUEL TYPE 1 | STANDARDS & TEST | SERVICE | ECS & SPECIAL FEATURES 3 | DIAGNOSTIC 5 | | | | |
|---|--|--|--|---|--|-------------------------------------|--|---------------------------------------|--|--|--|--|
| ILAN | | | | | PROCEDURE | CLASS | TWC, SFI, 2AFS, HO2S | | | | | |
| 2014 | 014 ERIIE06.8BW5 | | 6.8 | LPG | Otto | HDO | 100, 011, 2AI 0, 11020 | EIVID+ | | | | |
| | 'ENGINE'S IDLE NS CONTROL 4 | | | А | DDITIONAL IDLE EN | IISSIONS CON | ITROL 4 | | | | | |
| | N/A | | | | N | /A | | **** | | | | |
| ENGINE (L | L) | ENGINE MODELS / CODES (rated power, in hp) | | | | | | | | | | |
| 6.8 | BlueBird Vision School Bus / EEF618BR505, EEF61HBR505, EEF618BR510, EEF61HBR510, EEF61BBR511, EEF61HBR512, EEF61HBR512, EEF61BR512, EEF61HFR512, EEF61HFR512, EEF61HFR512, EEF61HFR512, EEF418YR505, EEF418YR505, EEF418YR511, EEF41LYR511, EEF41LYR511, EEF41LYR511, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41LYR512, EEF41BRF510, EEF418RR510, EEF418RR505, EEF61BAR505, EEF61BAR510, EEF61BAR510, EEF61HAR505, EEF61BAR510, EFF61BAR510, EFF61HAR510, EFF61BAR510, EFF | | | | | | | | | | | |
| * =not applic L=liter; hp= | cable; GVWR =gros =horsepower; kw =k | s vehicle v ilowatt; h | weight rating; 13 CCR : r=hour; | xyz=Title 13, California Co | de of Regulations, Sect | ion xyz; 40 CFF | R 86.abc=Title 40, Code of Federal Regulation | ons, Section 86.abc; | | | | |
| CNG/LN | NG=compressed/liqu | efied natu | ıral gas; LPG=liquefied | petroleum gas; E85=85% | ethanol fuel; MF=mult | i fuel a.k.a. BF: | bi fuel; DF=dual fuel; FF=flexible fuel; | | | | | |
| 2 | • | , | , , ., | an bus; HDO=heavy duty (| | | | | | | | |
| up catalyst; TBI=throttle super charg | DPF=diesel particular body fuel injection; ger; CAC=charge ai | late filter; SFI/MFI= r cooler; | PTOX=periodic trap of sequential/multi port fu | kidizer; HO2S/O2S=heater el injection; DGI=direct ga gas recirculation / cooled E | d/oxygen sensor; HAF | S/AFS=heated/a B=gaseous cart | tive catalytic reduction – urea / – ammonia; air-fuel-ratio sensor (a.k.a., universal or linea ouretor; IDI/DDI=indirect/direct diesel injecti njection; SPL=smoke puff limiter; ECM/PC | r oxygen sensor); on: TC/SC=turbo/ | | | | |
| ⁴ ESS=en (per 13 CCF | ngine shutdown syst R 1956.8(a)(6)(D); I | em (per 13 E xempt =e | 3 CCR 1956.8(a)(6)(A)(exempted per 13 CCR 1 | 1); 30g=30 g/hr NOx (per 956.8(a)(6)(B) or for CNG/ | 13 CCR 1956.8(a)(6)(C LNG fuel systems; N/A | ;); APS =interna =not applicable | al combustion auxiliary power system; ALT= (e.g., Otto engines and vehicles); | alternative method | | | | |
| EMD=e | engine manufacturer | diagnostic | c system ; OBD(F) / (P |) / (\$)=full / partial / partial | with fine / on-board diag | anostic; | | (2012-08-20 | | | | |

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

| in g/bhp-hr | NMHC | | NOx | | NMHC+NOx | | со | | PM | | нсно | |
|----------------|------|-----|------|-----|----------|-----|------|-----|-------|-----|-------|-----|
| | FTP | SET | FTP | SET | FTP | SET | FTP | SET | FTP | SET | FTP | SET |
| STD | 0.14 | * | 0.20 | * | * | * | 14.4 | * | 0.01 | * | 0.01 | * |
| CERT | 0.07 | * | 0.08 | * | * | * | 2.2 | * | 0.000 | * | 0.000 | * |
| NTE | * | | * | | * | | * | | * | | * | |

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;)

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 2035 et seq. (emission control warranty) and 13 CCR 1971.1 (on-board diagnostic).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-344-0047-6 dated November 14, 2014.

Executed at El Monte, California on this ______ day of December 2014.

Michael A Rog Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division