Ø Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	YEAR ENGINE FAMILY SIZES (2014 ELDRE06.8B10 6.8		ENGINE SIZES (L.)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6 EMD+				
			. ,	0.110		CLASS	SFI, HO2S, TWC, 2AFS					
			6.8	CNG	Otto	HDO	0.1,1.020,1.1.0,2.1.0					
PRIMARY ENGINE'S IDLI EMISSIONS CONTROL		ADDITIONAL IDLE EMISSIONS CONTROL 5										
N/A		N/A										
ENGINE (I	ENGINE MODELS / CODES (rated power, in hp)											
6.8		E450 Incomplete / DE418N05, DE418M05 (224 for all codes)										
L=liter; hp= CNG/LN L/M/H + ECS=er up catalyst; TBI=throttle super charg control mod ESS=er (per 13 CCI	=horsepower; kw=ki NG=compressed/liqu IDD=light/medium/hi mission control syste DPF=diesel particue body fuel injection; per; CAC=charge air fule; EM=engine mo ngine shutdown syste R 1956.8(a)(6)(D); E R 1956.8(a)(6)(D);	lowatt; his efied nature avy heav heav heav heav his efilter; SFI/MFI= cooler; Edification; em (per 13 exempt=e	r=hour; ral gas; LPG=liquef y-duty diesel; UB=u OC=three-way/oxidiz PTOX=periodic trap sequential/multi port EGR / EGR-C=exhau 2 (prefix)=parallel; 8 CCR 1956.8(a)(6)() xempted per 13 CCF	ied petroleum gas; E85=85% eth rban bus; HDO=heavy duty Otto; ting catalyst; NAC=NOx adsorpti oxidizer; HO2S/O2S=heated/ox; fuel injection; DGI=direct gasolir st gas recirculation / cooled EGR (2) (suffix)=in series; AMOX; am A)(1); 30g=30 g/hr NOx (per 13 C	anol fuel; MF=mult on catalyst; SCR-L /gen sensor; HAF- le injection; GCAR ; PAIR/AIR=pulsed monia oxidation ca CR 1956.8(a)(6)(C fuel systems; N/A	i fuel a.k.a. BF I / SCR-N=select S/AFS=heated/a B=gaseous car s/secondary air stalyst .); APS =internal s=not applicable	R 86.abc=Title 40, Code of Federal Regulation =bi fuel; DF=dual fuel; FF=flexible fuel; btive catalytic reduction – urea / – ammonia; air-fuel-ratio sensor (a.k.a., universal or linea buretor; IDI/DDI=indirect/direct diesel injection; SPL=smoke puff limiter; ECM/PC al combustion auxiliary power system; ALT= (e.g., Otto engines and vehicles); ic.	WU (prefix) =warm- r oxygen sensor); on; TC/SC=turbo/ M=engine/powertrain				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		со		PM		нсно	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	*	0.20	*	*	*	14.4	*	0.01	*	0.01	*
CERT	0.003	*	0.08	*	*	*	2.2	*	0.002	*	0.001	*
NTE	*		*		*		*		* .		*	

⁴ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic), and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of January 2014.

2Erik White, Chief

Mobile Source Operations Division