California	Environmental	Protection	Agency

OB Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMI	LY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES	DIAGNOSTIC 6
			312E3 (L)		PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, DOC,	OBD (\$)
2014	EVPTH16.10	601	16.1	Diesel	Diesel	HHDD	PTOX, SCR-U, AMOX	ΟΒΒ (ψ)
	YENGINE'S IDLE NS CONTROL 30g			ADDI'	TIONAL IDLE EN	MISSIONS CO	NTROL ⁵	
ENGINE (L	L)			ENGINE MODE	LS/CODES (ra	ted power, in	hp)	
16.1			-	See attachmen	t for engine m	odels and r	atings	

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

Limit HDD=lignt/medium/neavy neavy-duty diesei; UB=urban bus; HDD=neavy duty Otto; ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; AMOX = ammonia oxidation catalyst; DCC = Diesel Oxidation Catalyst ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel system; N/A=not applicable (e.g., Otto engines and vehicles); EMD=puipted fuel dengrating explore the approxement of the carbody differential vehices (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD (F/P/\$) = full/partial/partial with fine on-board diagnostic system (13 CCR 1971.1)

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

NM	нс	N	Ox	NMHC	C+NOx	C	0	P	М	HC	НО
FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	. *
*	*	*	*	*	*	*	*	*	*	*	*
0.0004	0.004	0.06	0.09	*	*	0.04	0.0	0.002	0.002	*	*
0.2	21	0.	30		*	19).4	0.	02		*
	FTP 0.14 * 0.0004	0.14 0.14	FTP SET FTP 0.14 0.14 0.20 * * * 0.0004 0.004 0.06	FTP SET FTP SET 0.14 0.14 0.20 0.20 * * * * 0.0004 0.004 0.06 0.09	FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * * * * * 0.0004 0.004 0.06 0.09 *	FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * * * * * * * * 0.0004 0.004 0.06 0.09 * * *	FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 * * * * * * * 0.0004 0.004 0.06 0.09 * * 0.04	FTP SET FTP SET FTP SET FTP SET 0.14 0.14 0.20 0.20 * * 15.5 15.5 * * * * * * * * 0.0004 0.004 0.06 0.09 * * 0.04 0.04	FTP SET FTP SET FTP SET FTP SET FTP 0.14 0.14 0.20 0.20 * * 15.5 15.5 0.01 * * * * * * * * * 0.0004 0.004 0.06 0.09 * * 0.04 0.00 0.002	FTP SET FTP SET FTP SET FTP SET FTP SET FTP SET <td>FTP SET FTP SET SET</td>	FTP SET

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test car CO=carbon monoxide; PM=particulate matter; HCHO=formaldehvde: FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen;

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted Dec. 12, 2002, as last amended April 18, 2013, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have ten deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$325 per engine for the third through tenth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2014 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the guarter in guestion, in which case all engines covered under this conditional certification for that guarter and all future guarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

California Environmental Protection Agency

VOLVO POWERTRAIN CORPORATION

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order. Executed at El Monte, California on this $24 \pm h$ day of December 2013.

en

Erik White, Chief Mobile Source Operations Division

			En	Engine Model	A TTACHMENT	Template	* *		A-242-0075
Engine Family	1.Engine Code	2.Engine Model	4. Fuel Rate: 3.BHP@RPM mm/stroke @ peak (SAE Gross) (for diesel only)	4.Fuel Rate: n/stroke @ peak HP (for diesel only)	kate: 5.Fuel Rate: peak HP (lbs/hr) @ peak HP 6.Torque @ RPM I only) (for diesels only) (SEA Gross)		7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
EVPTH16.1G01	50 State	D16J - 600	600 @ 1800	340.3	204.5	2103 @ 1000	383.6	128.1	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	D16J - 550	550 @ 1800	322.3	193.7	1898 @ 1000	346.1	115.6	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	D16J - 500	500 @ 1800	294.0	176.7	2128 @ 1000	326.4	109.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	D16J - 500	500 @ 1800	294.9	177.2	1902 @ 1000	346.6	115.7	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	MP10 - 605C	605 @ 1800	343.0	206.1	2108 @ 1000	385.1	128.6	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	MP10 - 565C	565 @ 1800	323.3	194.3	2009 @ 1000	366.3	122.3	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	MP10 - 525C	525 @ 1800	292.4	175.7	1919 @ 1000	349.7	116.7	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
EVPTH16.1G01	50 State	MP10 - 555M	555 @ 1800	319.5	192.0	2111 @ 1000	384.8	128.5	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX.
EVPTH16.1G01	50 State	MP10 - 515M	515 @ 1800	294.4	176.9	2018 @ 1000	368.4	123.0	TC, CAC, EGR, DDI, ECM, DOC, PTOX, SCR, AMOX
					والمستقد والمحافظة والمحافظة والمحافظة المحافظة والمحافظة والمحافظة والمحافظة والمحافظة والمحافظة				