Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC <sup>6</sup> R, OBD (\$)	
YEAR 2014		ENVXH07570SB		Diesel	PROCEDURE	CLASS 2	DDI, TC(2), CAC(2), ECM, EGR, OC, PTOX, SCR-U		
PRIMARY	ENGINE'S IDLE	i ang	12.4		DDITIONAL IDLE EN		5	u eleteren. Ledi jaiosci	
	30g				N	/A	TENTY VIOLEN		
ENGINE (	L)			ENGINE MO	DDELS / CODES (ra	ted power, in	hp)	BINDINGS.	
12.4	sy (coetto)	an te		ergency Vehicle Rat			0); A365/ Á365 (365) 62898 / A430 (430)	that eriarie Pureuant t	
L=liter; hp 1 CNG/L 2 L/M/H I 3 ECS=e up catalyst TBI=throttl super char control mo	=horsepower; kw=kil NG=compressed/lique HDD=light/medium/he mission control syster ; DPF=diesel particul e body fuel injection; ger; CAC=charge air	owatt; hr efied natu avy heav m; TWC/o ate filter; SFI/MFI= cooler; E	r=hour; ral gas; LPG=liquefie y-duty diesel; UB=urb OC=three-way/oxidizir PTOX=periodic trap o sequential/multi-port f	d petroleum gas; E85=85% ban bus; HDO=heavy duty ( ng catalyst; NAC=NOx adso oxidizer; HO2S/O2S=heated uel injection; DGI=direct gas t gas recirculation / cooled_E	ethanol fuel; MF=mul Otto; orption catalyst; SCR-l d/oxygen sensor; HAF soline injection; GCAF	ti fuel a.k.a. BF  J / SCR-N=sele S/AFS=heated/ RB=gaseous ca	R 86.abc=Title 40, Code of Federal Regulations ==bi fuel; DF=dual fuel; FF=flexible fuel;  cutive catalytic reduction – urea / – ammonia; W /air-fuel-ratio sensor (a.k.a., universal or linear or rburetor; IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM=	/U (prefix) =warm- xygen sensor); ; TC/SC=turbo/	
(per 13 CC	ngine shutdown syste	xempt=e	xempted per 13 CCR	(1); 30g=30 g/hr NOx (per 1956.8(a)(6)(B) or for CNG/ P) / (\$)=full / partial / partial	LNG fuel systems; N/A	A=not applicable	nal combustion auxiliary power system; ALT=al e (e.g., Otto engines and vehicles);	ternative method	

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
CERT	0.04	0.01	0.12	0.14	*	*	0.4	0.01	0.003	0.001	*	*
NTE	0.21		0.30		* .		19.4		0.02		*	

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= supplemental emissions testing; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted December 12, 2002, as last amended April 18, 2013, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine family is conditionally certified pending submission of additional test data to verify compliance with useful-life emission standards. The manufacturer has until April 30, 2014 to provide test data to confirm or correct the certification emissions levels on this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified pursuant to Health and Safety Code Section 43153 and subject to civil penalties pursuant to Health and Safety Code Section 43154.

BE IT FURTHER RESOLVED: That the manufacturer has elected to include engine models in this engine family which are identified for "emergency vehicle use only". These "emergency vehicle use only" engines are exempt from requirements imposed pursuant to California law and the regulations adopted pursuant thereto for motor vehicle pollution control devices per California Vehicle Code Section 27156.2. The manufacturer must clearly label these engines for "emergency vehicle use only" on the engines' emission control label.

@ Air Resources Board

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have twenty deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$500 per engine for the third through twentieth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2014 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of January 2014.

Erik White, Chief

Mobile Source Operations Division