## **⊘** Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAN	IILY	ENGINE	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6		
YEAR			SIZES (L)	Compressed Natural	PROCEDURE Diesel -	CLASS *	ECM	EMD		
2015	FCSTH0.51	NGH	0.51 KG/S	Gas	special cycle					
PRIMARY ENGINE'S IDLE  EMISSIONS CONTROL  ADDITIONAL IDLE EMISSIONS CONTROL										
EXEMPT N/A										
ENGINE (	ENGINE MODELS / CODES (rated power, in hp)									
0.51 KG/S				See attachmen	nt for engine m	odels and ra	atings			
*	*									
L=liter; hp 1 CNG/Li 2 L/M/H I 3 ECS=e up catalyst TBI=throtic super char control more	=horsepower; kw=k NG=compressed/liqu HDD=light/medium/h mission control syste t; DPF=diesel partict e body fuel injection; ger, CAC=charge aidule; EM=engine m	ilowatt; hi lefied natu eavy heav em; TWC/ ulate filter; SFI/MFI= ir cooler; I odification;	r=hour; ural gas; LPG=liquef ry-duty diesel; UB=u OC=three-way/oxidi; PTOX=periodic trap sequential/multi por EGR / EGR-C=exha 2 (prefix)=parallel;	ied petroleum gas; E85=85% eth irban bus; HDO=heavy duty Otto zing catalyst; NAC=NOx adsorpti o oxidizer; HO2S/O2S=heated/ox t fuel injection; DGI=direct gasolir ust gas recirculation / cooled EGR (2) (suffix)=in series;	ianol fuel; MF=mult con catalyst; SCR-L ygen sensor; HAF: ne injection; GCAR c; PAIR/AIR=pulsec	i fuel a.k.a. BF  I / SCR-N=seled  S/AFS=heated/ B=gaseous car  d/secondary air	R 86.abc=Title 40, Code of Federal Regulation =bi fuel; DF=dual fuel; FF=flexible fuel; ctive catalytic reduction – urea / – ammonia; V air-fuel-ratio sensor (a.k.a., universal or linear or buretor; IDI/DDI=indirect/direct diesel injection injection; SPL=smoke puff limiter; ECM/PCM	VU (prefix) =warm- oxygen sensor); ; TC/SC=turbo/ =engine/powertrain		
(per 13 CC	R 1956.8(a)(6)(D);	Exempt=e	exempted per 13 CCI	A)(1); 30g=30 g/hr NOx (per 13 0 R 1956.8(a)(6)(B) or for CNG/LNG	fuel systems; N/A	=not applicable	al combustion auxiliary power system; ALT=al e (e.g., Otto engines and vehicles);	ternative method		

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		со		PM		НСНО	
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
CERT	0.06	0.05	0.05	0.06	*	*	0.6	0.5	0.001	0.001	*	*
NTE	0.21		0.30		*		19.4		0.02		*	

<sup>4</sup> g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-25)

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Executed at El Monte, California on this \_\_\_\_\_\_

H CHELLE

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

## **Engine Model Summary Template**

4.Fuel Rate:

5.Fuel Rate:

Attachment 181

A-338-0014 12-11-14

7.Fuel Rate:

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	(lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	mm/stroke@peak torque		9.Emission Control eDevice Per SAE J1930
FCSTH0.51NGH	520193-300	65X-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	520193-600	65Y-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	529749-200	65W-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	529749-100	65Z-HBx-THxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	520193-400	65X-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	520193-500	65Y-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	529749-400	65W-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM
FCSTH0.51NGH	529749-300	65Z-HBx-VHxx	65kW@ 96,000	14517 Btu/min	N/A	N/A	N/A	N/A	ECM