California Environmental Protection Agency		EXECUTIVE ORDER A-021-0616
	CUMMINS INC.	New On-Road Heavy-Duty Engines
🕬 Air Resources Board		Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL	ENGINE FAMILY	ENGINE	FUEL TYPE	STANDARDS & TEST		ECS & SPECIAL FEATURES	DIAGNOSTIC 6		
TEAR		512E5 (L)		PROCEDURE	CLASS	TBI, TC, CAC, ECM, EGR, TWC,			
2015	FCEXH0540LBG	BG 8.9 CNG/LNG Diesel UB				HO2S			
PRIMARY	ADDITIONAL IDLE EMISSIONS CONTROL								
E	XEMPT	IEMPT N/A							
ENGINE (L) ENGINE MODELS / CODES (rated power, in hp)									
8.9	8.9 See attachment for engine models and ratings								
* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; hr=hour;									

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

2 L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

³ ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); Bil=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct dissel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR.C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; ESS=engine buttion system; (cat 13 CCP 1455 6/JO4) (AU1); 20=20 oths Nov (cat 2 CCP 1455 6/JO4)(AU1); 20=20 oths Nov (c

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NMHC		NOx		NMHC+NOx		CO		РМ		нсно		
g/bhp-hr	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET	
STD	0.14	0.14	0.20	0.20	•	*	15.5	15.5	0.01	0.01	*	* .	
CERT	0.09	0.04	0.13	0.01	•	*	9.8	8.0	0.002	0.001	*	*	
NTE	0.21		0.	0.30		*		19.4		0.02		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET= Supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

day of October 2014.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

EO#: A-021-0616 Attachment: Page 1-f1

10-14-2014.

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torqu	9.Emission Control JeDevice Per SAE J1930
FCEXH0540LBG	3518;FR93286	ISL G 250	250@2200	N/A	N/A	730@1300	N/A	N/A	HO2S, PCM, TWC,
FCEXH0540LBG	3518;FR93281	ISL G 280	280@2200	N/A	N/A	900@1300	N/A	N/A	H02S, PCM, TWC,
FCEXH0540LBG	3518;FR93278	ISL G 300	300@2100	N/A	N/A	860@1300	N/A	N/A	HO2S, CM TWC,
FCEXH0540LBG	3518;FR93275	ISL G 320	320@2100	N/A	N/A	1000@1300	N/A	N/A	H02S, POM, TWC,
FCEXH0540LBG	3518;FR94390	ISL G 250	250@2200	N/A	N/A	730@1300	N/A	N/A	HO2S, PCM TWC,
FCEXH0540LBG	3518;FR94385	ISL G 280	280@2200	N/A	N/A	900@1300	N/A	N/A	HO2S PCM, TWC,
FCEXH0540LBG	3518;FR94382	ISL G 300	300@2100	N/A	N/A	860@1300	N/A	N/A	HO2S, PCM, TWC,
FCEXH0540LBG	3518;FR94379	ISL G 320	320@2100	N/A	N/A	1000@1300	N/A	N/A	H02S, PCM, TWC,

N/A BPIICAC HONS