Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The hybrid engine produced by Cummins Inc. (Cummins) and the hybrid system produced by Allison Transmission Inc. (Allison) are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. The production hybrid engine and the production hybrid system shall be identical in all material respects as those for which certification is granted.

YBRID EN	IGINE M	ODEL		EXECUTIVE		STANDARDS &	INTENDE	ENGINE OBD	PRIMARY ENGINE'S IDL			
MANUFACTURER		YEAR	ENGINE FAMILY	ORDER NUMBER	FUEL TYPE	TEST PROCEDURE	SERVICE CL		EMISSIONS CONTROL			
CUMMINS INC.		2015	FCEXH0540LAT	A-021-0622-1	DIESEL	DIESEL	UB / UB-Hybri	d OBD(\$)	Exempt			
NGINE (L)	ECS & SPECIAL FEATURES			ENGINE MODELS / CODES (rated power, in hp)								
	DDI, TC, C		M, EGR, OC, PTOX, J, AMOX	ISL9 330 / SC91903 (310)								
			tichtam de la constitution de la	H	YBRID SYSTE	M DESCRIPTION		LALE BUT ALL	Marie Salle			
HYBRID SYSTEM MANUFACTURER		HYBRID SYSTEM MODEL YEAR	HYBRID SYSTEM MOD		S INTENDED SERVICE CLASS		NERGY STORAGE SYS	STEM HYBRID OBD COMPLIANCE				
ALLISON TRANSMISSION INC.		2015	H 40	EP, H 50 EP	UB	-Hybrid Nickel-Metal Hydrid Battery		de OBD(\$)				
					HYBRID E	NGINE MODELS / CO	DES					

* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt;

=liter; hp=horsepower; kw=kilowatt;
L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;
CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a BF=bi fuel; DF=dual fuel; FF=flexible fuel;
ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel
particulate filter; PTOX=periodic trap oxidizer; HO28/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel
injection; SFI/MF1=sequential/multi port fuel injection; DGI=direct gasoline injection; IDI/DDI=indirect/direct diesel injection; TCSC=turbo/ super charge; CAC=charge air cooler; EGR / EGRC=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification;
2 (prefix)=parallel; (2) (suffix)=in series;
EMD=engine modification periodic system (13 CCR 1971); EMD=engine many facturer disappetic system (13 CCR 1971); SMD=engine many factu

EMD=engine manufacturer diagnostic system (13 CCR 1971); EMD+=engine manufacturer diagnostic system (13 CCR 1971.1); OBD= on-board diagnostic system; OBD(F) / (P) / (\$)= on-board diagnostic full / partial / partial with a fine

ESS-engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles); (Aug 2

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.8; 2) the SET and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this Cummins' engine family. "Diesel" CO, SET and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For dual- and flexible-fuel, the CERT values in brackets [] are those when tested on conventional test fuel.)

	NMHC		NOx		CO		PM		нсно	
	FTP	SET	FTP	SET	FTP	SET	FTP	SET	FTP	SET
STD	0.14	0.14	0.20	0.20	15.5	15.5	0.01	0.01		
FEL		•	•	•	•		*	•	*	*
CERT	0.01	0.003	0.13	0.08	0.1	0.02	0.000	0.000	*	
NTE	0.21		0.30		19.4		0.02			

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; SET=Supplemental Emissions test; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: For the listed engine models Cummins has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) with the exception of monitoring of the hybrid system under 13 CCR 1971.1(g) (Monitoring Requirements For All Engines), and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: For the listed hybrid system Allison has submitted the materials to demonstrate certification compliance with 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) except 13 CCR 1971.1(e) Monitoring Requirements for Diesel/Compression-Ignition Engines, (f) Monitoring Requirements for Gasoline/Spark-Ignited Engines, and (i) Monitoring System Demonstration Requirements for Certification.

BE IT FURTHER RESOLVED: For the listed hybrid system Allison has submitted the materials to demonstrate certification compliance with 13 CCR 2035 et seq. (emission control warranty).

EXECUTIVE ORDER A-419-0004 New On-Road Engine and Hybrid System Page 2 of 2 Pages

BE IT FURTHER RESOLVED: The listed Cummins' hybrid engine models and Allison's hybrid system models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of the heavy-duty on-board diagnostic (HD OBD) system) because the HD OBD system of the listed hybrid engine and hybrid system models have been determined to have nine deficiencies. The listed hybrid engine models are approved with nine deficiencies and are subject to Cummins paying a fine for the third through ninth deficiencies in the listed engine family that is produced and delivered for sale in California. The listed hybrid system models are approved with twelve deficiencies and are subject to the Allison paying a fine for the second through twelfth deficiencies in the hybrid system model listed in this Executive Order that is produced and delivered for sale in California. The listed hybrid engine and hybrid system models are approved subject to Cummins and/or Allison paying a fine of \$500 per combined hybrid engine and system that is produced and delivered for sale in California under this Executive Order. On a quarterly basis, Cummins and Allison shall submit to the Air Resources Board reports of the number of engines and hybrid systems produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2015 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines and hybrid systems covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engi

BE IT FURTHER RESOLVED: The Allison hybrid system models listed on this Executive Order may only be used with Cummins' hybrid engine models listed on this Executive Order whose on-board diagnostic system have been approved as compatible.

BE IT FURTHER RESOLVED: Sales of the Cummins hybrid engine and Allison hybrid system models using any identification other than that listed, selling the hybrid engine or hybrid system models for an application not listed in this Executive Order, or selling any components of the hybrid engine and hybrid system models as an individual system separately shall be prohibited unless prior approval is obtained by Air Resources Board.

BE IT FURTHER RESOLVED: Hybrid Engines certified under this Executive Order shall conform to all applicable California emission regulations.

Hybrid systems certified under this Executive Order shall conform to applicable provisions of 13 CCR 1971.1 (on-board diagnostic system, full or partial compliance), 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2141, 2142, 2144-2146 (emissions warranty information report and field information report).

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

. 1 1

day of February 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division